

DGC DATA GUIDE CABLE

Electronic and Electrical Wire & Cable Products

232 Sherman Street Gardner, MA 01440
 Phone: 978-632-0900 Fax: 978-630-1872
 Visit us on our website; www.dataguidecable.com

**2 CONDUCTORS – 20 AWG
 AWM RATED 90C 1000 VOLTS**

CONDUCTORS:

- 20 AWG 7/.0121" TC with .018" Wall Thickness 90C 1000V Insulation Polyester Elastomer to a Nominal O.D. of .072" +/- .002"
- 2 Conductors Total
- Color Coded as Indicated
- Cable Twist with Minimum of 1 Twist per 3 Inches

BINDER:


- .001" Thickness Polyester

JACKET:

- .032" Nominal Wall Thickness (**Gray) 90C PVC to .210" Nominal Diameter
- ** Jacket must be Loose Enough to Slide 4" off Easily by Hand

CABLE CHARACTERISTICS:

- ** Cable Weight: 20lbs/1000'
- Capacitance (C to C): 28pf/ft
- Impedance: 86 OHMS Nominal
- Current Carrying Capacity: 3 AMPS



COLOR CODE

CONDUCTOR #	COLOR
1	BLACK
2	RED

Agency Approval

- UL AWM 10258/20886 90C 1000V
- CSA AWM 90C 1000V
- CE
- RoHS COMPLIANT

REVISION HISTORY

0	3/15/11	WD	FIRST ISSUE
1	4/8/11	WD	PRIME O.D.: .066" TO /072"
2	9/5/12	WD	NEW SPEC FORMAT

Customer Number	
D.G. Part Number	11C4-7
Prepared By:	KAM
Reviewed By:	WJD