



Issue Date: 8/27/2015

**Construction**

**C5571**

Issue: 1

<b>Description:</b>	<b>2/C 20 (10) TC mPPE/PUR</b>	<b>Diam. (In)</b>
<b>Component:</b>	2 Conductors	
<b>Conductor:</b>	20 AWG 10/30 Tinned Copper Smoothbunch	0.035"
<b>Insulation:</b>	0.010" Halogen Free mPPE (Modified Polyphenylene)	0.055"
<b>Color Code:</b>	Black, Red	0.055"
<b>Cable Assembly:</b>	2 Conductors Bunched Cabled	0.11"
<b>Fillers</b>	Fibrillated polypropylene or solid fillers for roundness (optional)	0.11"
<b>Tape:</b>	Non-Woven Separator Tape for Strip-Ability (optional)	0.113"
<b>Jacket:</b>	0.030" Halogen Free Polyurethane	0.173"
<b>Jacket Color:</b>	Gray	0.173"
<b>Print:</b>	E174416 RU AWM-21755 90°C 600V - - - cRU AWM I/II A B 90°C 600V FT-2	Apollo
<b>Black Ink</b>	Video Technology Zero Halogen Rail Cabling	

Specifications:	<u>AWM Style</u>	<u>Temp</u>	<u>Voltage</u>	<u>Flame</u>
<b>UL</b>	AWM- 21755	90°C	600V	FT-2
Canadian cRU	AWM	90°C	600V	FT-2

**Environmental Compliance**

- EU Directive 2011/65/EC(RoHS):
- REACH Regulation (EC 1907/2006):
- California Prop 65: