

Aerospace Part#: 1268/19y604

CONTROL CABLE

DESCRIPTION

2 Conductors AWG 20/19x32 TC
Overall Braid Shield Fiberglass Filler FEP/FEP Yellow

PHYSICAL PROPERTIES

Conductors

Insulation

# Conductors	AWG	Material	Material	Wall	Finished OD
2	20/19x32	Tinned Copper	FEP	.009"	.056"

Outer Braid Material

Layer 1 Type	Material	AWG
Overall Braid Shield	Tinned Copper	36

Outer Jacket Material

Cabling

Jacket Material	Color	Wall	Overall O.D.	Lay
FEP	Yellow	.025"	.190" Nom.	1.5" Lay on Pair with 2 TFE Coated Fiberglass Filler + .001"Clear Mylar Binder

MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius
Rated -80C to 200C	32.3 lbs / m	10 X OD

ELECTRICAL PROPERTIES

Max. Operating Voltage
Rated 300 Volts

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

Reach / RoHS Compliant	YES
Suitability	Indoor, Wet location
Resistance	Oil, Gas, Sunlight, Abrasion, Acid

MISCELLANEOUS

Color Black / White /
Code:

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

* Specification subject to error and may change without notice