


## 83393 Multi-Conductor - Control and Instrumentation Cable, 2 Conductors Cabled



For more Information  
please call

1-800-Belden1



### General Description:

20 AWG stranded (7x28) TC conductors, twisted pair, 20 AWG (7x28) stranded TC drain wire, FEP insulation, special Beldfoil® shield (100% coverage), silicone rubber jacket, noise reducing tape.

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
2	20	7x28	TC - Tinned Copper

Total Number of Conductors: 2

#### Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
FEP - Fluorinated Ethylene Propylene	0.508

#### Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100
1		Tape	Noise Reducing Conductive Nylon	

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
20	7x28	TC - Tinned Copper

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
Silicone Rubber	0.9398

#### Overall Cable

Overall Cabling Fillers: Fiberglass yarn

Overall Cabling Lay Length & Direction:

Length (mm)	Direction	Twists (twist/m)
41.275	Left Hand	24.279

Overall Cabling Color Code Chart:

Number	Color
1	Black
2	Red

Overall Nominal Diameter: 6.147 mm

### Mechanical Characteristics (Overall)

Operating Temperature Range: -70°C To +150°C

Bulk Cable Weight: 53.575 Kg/Km

Max. Recommended Pulling Tension: 112.095 N

Min. Bend Radius/Minor Axis: 63.500 mm

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

AWM Specification: UL Style 4516 (600 V 150°C)

EU Directive 2011/65/EU (ROHS II): Yes

EU CE Mark: Yes

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

## METRIC MEASUREMENT VERSION

### 83393 Multi-Conductor - Control and Instrumentation Cable, 2 Conductors Cabled

EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Other Specification:	NEMA HP3

#### Flame Test

UL Flame Test:	VW-1 (Singles)
----------------	----------------

#### Suitability

Suitability - Indoor:	Yes
-----------------------	-----

#### Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

### Electrical Characteristics (Overall)

#### Nom. Inductance:

Inductance ( $\mu\text{H}/\text{m}$ )
0.6562

#### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
72.182

#### Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/m)
131.24

#### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
34.4505

#### Max. Operating Voltage - UL:

Voltage	Description
600 V RMS	UL AWM 4516

#### Max. Operating Voltage - Other:

Voltage	Description
2000V DC	Shield to ground through jacket

#### Max. Recommended Current:

Description	Current
10C Temperature Rise	3.8 Amps per conductor @ 25°C ambient

### Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
83393 004500	500 FT	19.500 LB	YELLOW	C	1 PR #20 FEP FS SIL

#### Notes:

C = CRATE REEL PUT-UP.

Revision Number: 3 Revision Date: 08-06-2013

© 2015 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein. All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.