



Specification Sheet

Lake Cable Quote Part #: C202S-2463-XX

Description: 20 AWG 2 conductors 7 strands tinned copper, PE insulated, an aluminum/mylar shield with a tinned copper drain wire and an overall PVC jacket approved 600V, 80°C (UL) AWM 10514 / 2463.

1. Conductor

- 1.1. AWG Size & Stranding: 20 AWG 7 Strands Class B
- 1.2. Material: Annealed Tinned copper
- 1.3. Conductor Count: 2 Conductors

2. Dielectric

- 2.1. Material: Polyethylene
- 2.2. Wall Thickness: 0.020"
- 2.3. Color Code: Black, Red

3. Assembly

- 3.1. Cable Lay Length: 2.50" LHL
- 3.2. Cable Fillers: N/A
- 3.3. Binder: N/A
- 3.4. Shield: Aluminum/Mylar Tape - 100% coverage
- 3.5. Drain Wire: 22 AWG 7 Strand Tinned Copper

4. Jacket

- 4.1. Material: Polyvinylchloride
- 4.2. Wall Thickness: 0.035"
- 4.3. Diameter: 0.225"
- 4.4. Color: Gray, Black, Brown, Red, Orange, Yellow, Blue, Violet
- 4.5. Ripcord: Yes
- 4.6. Weight: 27 Lbs/Mft

5. Markings

- 5.1. Type: Cable permanently identified via surface inkjet print with white ink
- 5.2. Legend: LAKE CABLE E206787 20AWG 2C SHIELDED 2U AWM 2463 600V 80°C
600V "ROHS II" REACH MADE IN USA
- 5.3. Footage Markers: Yes

6. Standards

- 6.1. UL recognized AWM Style 2463 600V 80°C
- 6.2. Insulated conductors per UL AWM Style 10514
- 6.3. All materials used in the manufacture of this cables are RoHS compliant

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION