



# Specification Sheet

## Lake Cable Quote Part #: 140211WGP11

**Description:** 20 AWG 2 conductors 7 strands tinned copper, PE insulated, an aluminum/mylar shield with a tinned copper drain wire and an overall PVC jacket approved 600V, 80°C (UL) AWM 10514 / 2463.

### 1. Conductor

- 1.1. AWG Size & Stranding: 20 AWG 7 Strands Class B
- 1.2. Material: Annealed Tinned copper
- 1.3. Conductor Count: 2 Conductors

### 2. Dielectric

- 2.1. Material: Polyethylene
- 2.2. Wall Thickness: 0.020"
- 2.3. Color Code: Black, Red

### 3. Assembly

- 3.1. Cable Lay Length: 2.50" LHL
- 3.2. Cable Fillers: N/A
- 3.3. Binder: N/A
- 3.4. Shield: Aluminum/Mylar Tape - 100% coverage
- 3.5. Drain Wire: 22 AWG 7 Strand Tinned Copper

### 4. Jacket

- 4.1. Material: Polyvinylchloride
- 4.2. Wall Thickness: 0.035"
- 4.3. Diameter: 0.225"
- 4.4. Color: Gray
- 4.5. Ripcord: Yes
- 4.6. Weight: 27 Lbs/Mft

### 5. Markings

- 5.1. Type: Cable permanently identified via surface inkjet print with white ink
- 5.2. Legend: LAKE CABLE E206787 20AWG 2C SHIELDED RU AWM 2463 600V 80°C  
600V "ROHS II" REACH MADE IN USA
- 5.3. Footage Markers: Yes

### 6. Standards

- 6.1. UL recognized AWM Style 2463 600V 80°C
- 6.2. Insulated conductors per UL AWM Style 10514
- 6.3. All materials used in the manufacture of this cables are RoHS compliant

**Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.**

Signature
Company

**ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION**