

Aerospace Part#: 1260ijcls

CONTROL CABLE

**DESCRIPTION**

2 Conductors AWG 20/7x28 TC  
Overall Foil Shield FEP/FEP Clear

**PHYSICAL PROPERTIES**

**Conductors**

**Insulation**

# Conductors	AWG	Material	Material	Wall	Finished OD
2	20/7x28	Tinned Copper	FEP	.018"	.074"

**Outer Shield Material**

**Drain Wire**

Layer 1 Type	Material	Coverage	AWG	Material
Overall Foil Shield	Alum / Mylar	100%	22/7x30	Tinned Copper

**Outer Jacket Material**

**Cabling**

Jacket Material	Color	Wall	Overall O.D.	Lay
FEP	Clear	.015"	.182" Nom.	2" Lay on Cable

**MECHANICAL PROPERTIES**

Operating Temp	Total Weight	Bend Radius
Rated -80C to150C	23.9 lbs / m	10 X OD

**ELECTRICAL PROPERTIES**

Max. Operating Voltage
Rated 300 Volts

**INDUSTRY APPROVALS AND COMPLIANCE**

**Standards & Environmental Programs**

Reach / RoHS Compliant	YES
Suitability	Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasion, Acid

**MISCELLANEOUS**

Markings: DIYAUTOTUNE.COM WHITE:CRANK CKP+/RPM INPUT BLACK:CKP- (SEQ#)

Color Code: Black / White /

**Contact Us For More Information**

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

\* Specification subject to error and may change without notice