

AEROSPACE WIRE & CABLE, INC.
129-09 18TH AVENUE
COLLEGE POINT, NY 11356
(718) 358-2345
FAX (718) 358-2522

CABLE SPECIFICATIONS

CUSTOMER : SHIP DATE :
PART NUMBER : 1264JM QUANTITY :

1) DESCRIPTION : 2 Conductors Foil & Braid With Drain CMP (UL AWM Style
AWG 20/7x28 TC FEP/FEP Tan 20229)

2) CONDUCTOR : AWG 20/7x28 Tinned Copper O.D.= .038" Nom.

3) INSULATION : FEP .010" Wall O.D.= .056"-.060"

4) COLOR CODE : Black / White

5) TWIST LAY : 2" Lay on Cable

6) SHIELD : Aluminum/Mylar/Aluminum With AWG 22/7x30 TC Drain Wire

7) BRAID : Overall Tinned Copper Braid with 70% Coverage AWG 34

8) JACKET : Tan FEP .027" Wall O.D.= .204" Nom.

9) MARKING : E130356 TYPE CMP-E157093 UL AWM STYLE 20229 300V,

10) CAPACITANCE: n/a (20 AWG (UL), C(UL) 150C

11) WEIGHT : 42 Lbs / 1000 Feet (Operating Range -80 C to 200 C)

12) TEMPERATURE: UL Rated -80 C to 150 C VOLTAGE: UL 300V Power Ltd.