

2002 P-96C



# Product Data Sheet



Part Number: 92782A

Revision: 2/12/2014

1PR 20AWG PVC, UNSH, PVC

SOUND, ALARM AND SECURITY

## A. CONSTRUCTION

Conductor: #20 AWG (7/28) Tinned Copper  
 Insulation: .008" Wall, Plenum PVC  
 Cable Assembly: 2 Conductors with a 6.00" LML  
 Ripcord: Plenum Ripcord  
 Jacket: .015" Wall, Plenum PVC  
 Jacket Color: White (Munsell Centroid)  
 Sequential Footage: Yes  
 Print Legend: LOGISON(TM) / ACCUMASK(TM) - E60233-B 1 PAIR 20 AWG (UL) CL3P / (UL)C(UL) CMP 75C FT6 ROHS (date code - MM/YY) (sequential footage)

## DIAMETERS

.036" Nom  
 .052" Nom  
 .104" Nom  
 .136" ± .012"

## B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL 444 / CSA C22.2 No. 214	Type CMP
National Electrical Code	Article 725
UL Standard 13	Type CL3P
Flame Compliances:	
NEC Type CMP, CL3P	NFPA 262
CEC Type CMP	CSA FT6

## C. ELECTRICAL PROPERTIES

Temperature:	0°C to +75°C
Suggested Working Voltage:	300 Vrms (Max)
Conductor DCR:	10.9 Ohms/1000ft (Max) @ 20°C
Capacitance (Cond-Cond):	31.8 pF/ft @ 1kHz (Nom)
Characteristic Impedance:	61 Ohms @ 1MHz (Nom)

## D. COLOR CODE

PAIR	COLOR 1	COLOR 2
1	BLACK	WHITE

## E. CUSTOMER APPROVAL

Signature: Alex Date: 6/10/2014

Note: Data subject to change without notice. Contact your Customer Service representative for latest information.