



# SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896  
Fax: 613-394-4101 email: info@electrocables.com  
Mailing: P.O. Box 276, Trenton, ON K8V 5R5  
www.electrocables.com

25-Nov-2013

Product Number : **5152051TFT4.1**

**RoHS**

**O/A SH CABLE 1/PR 20/7 AWG STC  
SR-PVC Insulation  
Black PVC FT-4 Jacket**

Conductor : 20 AWG 7 Strand STC Cond.

Total Cable Weight : 41 kg/km	Final Diameter : 0.206 inches
Insulation : SR-PVC	Jacket : PVC
Shield : Foil Shield 0.625	
Drain : 20 AWG 7 Strand STC Cond.	
DC Resistance 25°C: 10.7 Ohms / 1000 ft	Mutual Capacitance : 35.6 pF/ft
Impedance : 60 Ohms	Cond to Shield Cap. : 68.2 pF/ft
Velocity of Prop : 58 %	Inductance. : 1.6 mH/km

Print Notes :

Standard Print : ECI CSA CMG 105°C OR AWM II A/B 105°C LL61365 600V FT-4 RU AWM  
E107863 STYLE 2464 300V VW-1 20 AWG RoHS

*(All of the above values are approximated to within 10%)*