

Description: One 20 AWG Twisted Pair
 Overall Foil Shield and PVC Jacket

Date: 2/1/2008

JM Part Number: JM55347
Reference: TBD

Components Two 20 AWG Insulated Conductors

Conductor: 20 AWG, 7/28 tinned copper

Insulation: .020" nominal wall of PVC (see color code) .078"

Overall Cable Construction


Cabling: Two conductors twisted together (fillers, as necessary, for roundness)

Drain Wire: 20 AWG, 7/28 tinned copper

Shield: Aluminum-Mylar tape, Aluminum side IN

Jacket: .045" nominal wall of Gray PVC .249"

Print

E66440  AWM 21098 90C 600V 60C OIL 1/PR 20 AWG SHIELDED
 --- LL41103 CSA AWM I/II A/B 90C 600V FT1

Color Code

1. Black

2. Red

Requirements

Temperature: 90°C
 Voltage: 600V

Approvals: UL AWM Style 21098 (60C OIL)
 CSA AWM, FT1

Weights

Approximate Shipping Weight: 39 Pounds Per 1000 Ft Put-Up

Approximate Copper Weight: 10.8 Pounds Per 1000 Ft

Written By:	rjc	2/1/2008	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				