



GENERAL PRODUCT SPECIFICATION
 Phone 800-316-8877 Fax 878-368-1275
 www.jamesmonroewire.com

Description: Three Conductor, 20 AWG
 Overall Black PVC Jacket

Date: 1/23/2009

Part Number: JM54946
 Reference: W1079

Components Three 20 AWG Insulated Conductors

Conductor: 20 AWG, 19/32 bare copper

Insulation: .010" nominal wall of PVC .059"

Release Agent: Release agent applied to prevent bonding of conductors to jacket

Cable Construction

Cabling: Three insulated conductors twisted together, no fillers

Jacket: .032" nominal wall of pressure extruded Black PVC .190" ± .005"

Color Code

1. Black 2. White 3. Green

Print

Jacket to be printed with White ink as follows:

CANFIELD CONNECTOR W1079 20/3 E66440 A AWM 2464 80C 300V VW-1
 LL41103 CSA AWM I/II A 80C 300V FT1

Requirements

Temperature: 80C
 Voltage: 300V

Approvals: UL AWM Style 2464
 CSA AWM, FT1

2003C-05m1
273104
APPROVED
[Signature]
 1/26/09

Written By:	rjc	1/23/2009	Rev. 0	Initial Issue
Revised By:				
Revised By:				
Revised By:				