

H03VV-F



H03VV-F is a harmonized, light duty, flexible, PVC insulated, black or white PVC jacketed multi-conductor 300V. European cord. Recommended for use in connecting small electrical appliances under low mechanical stresses environments as in offices, kitchens and households. H03VV-F can commonly be found in connections to kitchen utensils, desk lamps, floor lamps, vacuum cleaners, office machines and radios. These cables should NOT be used in cooking and heating apparatus.



- **BENDING RADIUS:** 7.5 x Cable Diameter
- **TEMPERATURE:** -30° C. to +70° C. (Flame protection to IEC 60332.1)
- **RATED VOLTAGE:** Nominal 300/300V.
- **STRANDING:** DIN VDE-0295 Class-5 fine bare copper strand.
- **COLOR CODE:** DIN VDE-0293-308
- **APPROVALS:** <HAR> HD 21.5 S3, DIN VDE-0281 Part 5, CE Low-Voltage Directive & ROHS compliant.

PART NUMBER	CORES	NOMINAL OD	LBS/MFT	KG/KM
20 AWG (16/32) 0,50mm²				
4022002*	2	0.201" / 5.1mm	27	40
4022003*	3	0.217" / 5.5mm	33	49
4022004*	4	0.236" / 6.0mm	41	61
18 AWG (24/32) 0,75mm²				
4021802*	2	0.213" / 5.4mm	33	49
4021803*	3	0.224" / 5.7mm	40	59
4021804*	4	0.248" / 6.3mm	48	72
4021805*	5	0.280" / 7.1mm	58	87
4021806*	6	0.307" / 7.8mm	66	98
4021807*	7	0.315" / 8.0mm	72	108

* Also available in White PVC jacket (403) ** For larger than 18 AWG sizes see H05VV-F (400)