SPECIALTY & CUSTOM CABLES

232 Sherman Street Gardner, MA 01440 Phone: 978-632-0900 Fax: 978-630-1872 Visit us on our website; www.dataquidecable.com

3 CONDUCTOR 20 AWG PVC/PVC O/A SHIELDED 80C 600VOLT

CONDUCTORS

<u>(3 TOTAL):</u>

- 20 AWG (7x28) Tinned Annealed Copper Insulated with .025" Nominal Wall of PVC to a Nominal O.D. of .088"

COLOR CODE:

- As Indicated


NOTES:

- 3" Nominal Left-Hand Direction Cable Lay
- Overall .002" Thickness Polyester Binder
- 20 AWG 7/28 Tinned Copper Drain
- Overall .0012" Thickness Aluminum/Polyester Shield, Foil Facing Inward
- Overall .045" Nominal Wall Black Pressured PVC Jacket to .289" Final

2003COBS-9DGF

00K10-5

- Diameter (.310" Absolute Max)
- Surface Printed in White Ink: "TOMAR M913"



COLOR CODE

CONDUCTOR	COLOR
1	BLUE
2	ORANGE
3	YELLOW

LISTINGS/AGENCY APPROVAL

- RoHS COMPLIANT

REVISION HISTORY

0	4/9/19	WJD	FIRST ISSUE

CUSTOMER APPROVAL (AS APPLICABLE)
---------------------	----------------

Title: ___

Date: ___

Reviewed By: WJD

Customer Number

D.G. Part Number

Prepared By: LLJ

DGCS001