

**ALPHA WIRE  
CUSTOMER PRODUCT SPECIFICATION**

Part Number: 810290  
Page 1 of 2 Pages

Issue: 1  
Issue Date: 2/7/2013  
Effective Date: 4/4/2013

- A. Construction** **Diameters (In)**
- 1) Component 1 **4 X 1 COND**
- a) Conductor 20 (7/28) AWG TC 0.038
- b) Insulation 0.016" Wall, Nom. PVC 0.070
- (1) Print ALPHANUMERIC NUMBERS - 1-ONE ALTERNATING AND INVERTED
- (2) Color Code Alpha Wire Color Code J1

Cond	Color	Cond	Color	Cond	Color
1	SLACK #1	3	BLUE #3		
2	RED #2	4	ORANGE #4		

- 2) Cable Assembly 4 Components Cabled
- a) Twists: 5.0 Twists/foot (min)
- b) Core Wrap Nonwoven Polyester Tape, 25% Overlap, Min.
- 3) Jacket 0.032" Wall, Nom. PVC 0.238 (0.249 Max.)
- a) Color(s) SLATE
- b) Ripcord 1 End 810 Denier Nylon
- c) Print ALPHA WIRE - P/N 810290 4C 20-AWG  
POWER EATON (UL) TYPE CM 105C OR AWM 2464 VW-1  
LLXXXXXX CSA 105C TYPE CMG FT4 CE  
ROHS (SEQ FOOTAGE)  
\* = Factory Code  
*[Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]*

**B. Applicable Specifications**

- 1) UL
- a) Component 1 AWM/STYLE 1569 105°C / 300 V<sub>RMS</sub>
- b) Overall AWM/STYLE 2464 80°C / 300 V<sub>RMS</sub>
- CM 105°C
- VW-1
- 2) CSA International CMG 105°C
- FT4
- 3) CE EU Low Voltage Directive 2006/95/EC

**C. Environmental Compliance**

- 1) CE EU Directive 2011/65/EU (RoHS2):  
This product complies with European Directive 2011/65/EU (RoHS Directive) of the European Parliament and of the Council of 8 June 2011. No Exemptions are required for RoHS Compliance on this item. Consult Alpha Wire's web site for RoHS C of C.
- 2) REACH Regulation (EC 1907/2006):  
This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item. For up-to-date information, please see Alpha's REACH SVHC Declaration.
- 3) California Proposition 65: The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.

**D. Physical & Mechanical Properties**

- 1) Temperature Range -30 to 105°C
- 2) Bend Radius 10X Cable Diameter
- 3) Pull Tension 35 Lbs, Maximum
- 4) Sunlight Resistance Yes

**E. Electrical Properties** (For Engineering purposes only)

- 1) Voltage Rating 300 V<sub>RMS</sub>
- 2) Capacitance 30 pF/ft @1 KHz, Nominal Conductor to Conductor
- 3) Inductance 0.19 µH/ft, Nominal
- 4) Conductor DGR 10.2 Ω/1000ft @20°C, Nominal

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides this information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE  
CUSTOMER PRODUCT SPECIFICATION


Part Number: 810290  
Page 2 of 2 Pages

Issue: 1  
Issue Date: 2/7/2013  
Effective Date: 4/4/2013

F. Other

- 1) Packaging \_\_\_\_\_ Flange x Traverse x Barrel (Inches)  
a) Bulk(Made-to-order)  
2) Notes:  
a) Same as 5054C except color code J1.

This Design is custom, Made-To-Order & once accepted, the order is NON-CANCELLABLE & NON-RETURNABLE.

Accepted By: 	Date: 2-11-13
Company: NEWTECH 3	Title: Buyer

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.