



Issue Date: 8/27/2015

Construction

C5570

Issue: 1

Description: 4/C 20 (10) TC mPPE/PUR		Diam. (In)
Component:	4 Conductors	
Conductor:	20 AWG 10/30 Tinned Copper Smoothbunch	0.035"
Insulation:	0.010" Halogen Free mPPE (Modified Polyphenylene)	0.055"
Color Code:	Black, Red, White, Green	0.055"
Cable Assembly:	4 Conductors Bunched Cabled	0.133"
Fillers	Fibrillated polypropylene or solid fillers for roundness (optional)	0.133"
Tape:	Non-Woven Separator Tape for Strip-Ability (optional)	0.136"
Jacket:	0.030" Halogen Free Polyurethane	0.196"
Jacket Color:	Gray	0.196"
Print:	E174416 RU AWM-21755 90°C 600V - - - cRU AWM I/II A B 90°C 600V FT-2	Apollo
Black	Video Technology Zero Halogen Rail Cabling	
Specifications:	<u>AWM Style</u> <u>Temp</u> <u>Voltage</u> <u>Flame</u>	
UL	AWM- 21755 90°C 600V FT-2	
Canadian cRU	AWM 90°C 600V FT-2	
Environmental Compliance		
<ul style="list-style-type: none"> • EU Directive 2011/65/EC(RoHS): • REACH Regulation (EC 1907/2006): • California Prop 65: 		