



Hach 1W1127

Specification

C5466

Hueson Wire
 38 Sutton Street
 Northbridge, MA 01534
 508-234-6372
 www.huesonwire.com

Issue Date: 1/15/2015

Issue: 2

Construction

Description: 4 Cond 20 AWG Electronic Cable		Diam (mm)	Diam. (In)
Component:	4 Conductors		
Conductor:	20 AWG 19/32 Tinned Copper to ASTM B-8	1,02mm	0.04"
Insulation:	0.016" (0,41mm) Premium Grade PVC	1,83mm	0.072"
Color Code:	Red, Blue, Green, Yellow	1,83mm	0.072"
Cable Assembly:	4 Conductors Bunched Cabled	4,42mm	0.174"
Fillers	Fibrillated Polypropylene or solid core for roundness (optional)	4,42mm	0.174"
Drain Wire:	No Drain	4,42mm	0.174"
Tape:	Polyester Separator Tape	4,50mm	0.177"
Braid:	Tinned Copper Braid Shield 90% (9E 34 A'	5,03mm	0.198"
Jacket:	0.045" (1,15mm) PVC Jacket (Oil, Moisture Resistant)	7,32mm	0.282"
Jacket Color:	Black	7,32mm	0.282"

Print: No Print Required

Specifications: This cable requires no agency approvals but will be built in accordance to UL specifications

105°C 600V VW-1

Environmental Compliance

EU Directive 2011/65/EC(RoHS):

All materials used in the manufacture of this part are in compliance with EU Directive 2011/65/EC regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.

REACH Regulation (EC 1907/2006):

This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.

California Prop 65:

The outer surface materials used in the manufacture of this part meet the requirements of California Prop. 65.



Hach 1W1127

Specification

C5466

Hueson Wire
38 Sutton Street
Northbridge, MA 01534
508-234-6372
www.huesonwire.com

Issue Date: 1/15/2015

Issue: 2

Drawing/Rotation:

