



Specification Sheet

Lake Cable Part #: S202PRST-IEW (420-X10R)

Description: 20 AWG 2 pair 10 strands tinned copper wire, PVC insulation, aluminum foil shield, drain wire Paper separator, with an overall PVC jacket. 105°C rated.

- 1. Conductor**
 - 1.1. AWG Size & Stranding: 20 AWG 10 Strands Class B
 - 1.2. Material: Annealed Bare Copper
 - 1.3. Conductor Count: 2 Pairs
- 2. Insulation**
 - 2.1. Material: Polyvinylchloride
 - 2.2. Wall Thickness: 0.009"
 - 2.3. Color Code: Red, Black, Yellow, White
- 3. Assembly (Pair)**
 - 3.1. Cable Lay Length: 2.00" LHL (6.0 Tw/Ft)
 - 3.2. Colors: Red & Black - Yellow & White
 - 3.3. Cable Drain Wire: 20 AWG 7 Strands Tinned Copper Drain (Drain Inside Foil) Each pair
 - 3.4. Cable Shield: Aluminum/Mylar - 100% Coverage (Foil facing In) Each pair
 - 3.5. Filler: Fibrillated Poly Filler
- 4. Overall Cabling**
 - 4.1. Cable Lay Length: 3.50" LHL (3.4 Tw/Ft)
- 5. Jacket**
 - 5.1. Separator: Tissue paper - 100% Coverage
 - 5.2. Material: Pressure Extruded Polyvinylchloride
 - 5.3. Wall Thickness: 0.030"
 - 5.4. Diameter: 0.230" +/- .005"
 - 5.5. Color: Black
 - 5.6. Weight: 35 Lbs/Mft
- 6. Markings**
 - 6.1. Legend: N/A
- 7. Standards**
 - 7.1. All materials used in the manufacture of this cable are RoHS II & REACH compliant
 - 7.2. Maximum operating voltage: 300V
 - 7.3. Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION