

ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Number: 669175
Page 1 of 1 Pages
CDC #: 1675

Issue: 2
Issue Date: 4/8/2004
Effective Date: 4/8/2004

General Description

Individual Component 1: 5 X 1 COND
Conductor: 20 (41/36) AWG TC
Insulation: 0.010" WALL SR-PVC
Color Code: 5 SOLID COLORS: Black, White, Red, Brown, Green

Overall

Cabling: 5 COMPONENTS CABLED
Core Wrap: CM TAPE
Jacket: 0.040" WALL BLACK PVC
Nominal Diameter: 0.240"
Packaging: 1000FT PUTUP

Print Legend: ALPHA WIRE - * P/N 669175 5C 20 AWG (UL)
TYPE CM OR AWM 2661 105C 300V LLXXXXX CSA
TYPE CMG OR AWM IA/B IIA/B FT4 105C 300V
CONTINUOUS USE FLEXIBLE CABLE CE**

Performance & Ratings

Temperature: 105 C
Voltage: 300 V_{RMS}
UL: AWM/STYLE2661
CM
CSA: AWM-I-A/B-II-A/B
CMG
FT4
MIL: NONE
CE: YES

Requested Quantity: 50,000Ft., 100,000Ft.

Application Notes

1. Bulk reels
2. Similar to Alpha P/N 86305CY except unshielded and 20 AWG 41/36 TC.

This Design is custom, Made-To-Order & once accepted, the order is NON-CANCELLABLE & NON-RETURNABLE.

Accepted By:	Date:
Company:	Title:

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.