



Issue Date: 8/27/2015

**Construction**

**C5572**

Issue: 1

<b>Description:</b> 5/C 20 (10) TC mPPE/PUR		<b>Diam. (In)</b>
<b>Component:</b>	5 Conductors	
<b>Conductor:</b>	20 AWG 10/30 Tinned Copper Smoothbunch	0.035"
<b>Insulation:</b>	0.010" Halogen Free mPPE (Modified Polyphenylene)	0.055"
<b>Color Code:</b>	Black, Red, White, Green, Orange	0.055"
<b>Cable Assembly:</b>	5 Conductors Bunched Cabled	0.149"
<b>Fillers</b>	Fibrillated polypropylene or solid fillers for roundness (optional)	0.149"
<b>Tape:</b>	Non-Woven Separator Tape for Strip-Ability (optional)	0.152"
<b>Jacket:</b>	0.030" Halogen Free Polyurethane	0.212"
<b>Jacket Color:</b>	Gray	0.212"
<b>Print:</b>	E174416 RU AWM-21755 90°C 600V - - - cRU AWM I/II A B 90°C 600V FT-2	
<b>Black Ink</b>	Apollo Video Technology Zero Halogen Rail Cabling	
<b>Specifications:</b>	<u>AWM Style</u>	<u>Temp</u>
<b>UL</b>	AWM- 21755	90°C
		600V
		FT-2
<b>Canadian cRU</b>	AWM	90°C
		600V
		FT-2
<b>Environmental Compliance</b>		
<ul style="list-style-type: none"> <li>• EU Directive 2011/65/EC(RoHS):</li> <li>• REACH Regulation (EC 1907/2006):</li> <li>• California Prop 65:</li> </ul>		