


Sheet	1 OF 1
P/N	N64392
Rev	A
Org.EN	117582
Rev.EN	118049

Original Equipment Manufacturer (OEM)

Description	CABLE 6 X 20 AWG SHIELD	
-------------	-------------------------	---

Suggested Vendor	ELECTROCABLES
Vendor P/N	5152006TFT4
Ordering Unit	ME

TECHNICAL CHARACTERISTICS

STRANDED TINNED COPPER CABLE

SR-PVC INSULATION, 100% ALUMINIUM FOIL SHIELD
STRANDED TINNED COPPER DRAIN, GREY PVC JACKET FT-4

- NUMBER OF WIRE : 6
- AWG SIZE : 20
- STRANDING : 7/28
- INSULATION THICKNESS : 0.01"
- JACKET THICKNESS : 0.023"
- NOMINAL O.D. : 0.287"
- CABLE MASS : 141 LB/1000 FT
- OPERATING TEMPERATURE : -20°C TO 105°C
- DRAIN WIRE SIZE : 22 AWG
- WIRE COLOR BLACK
 WHITE
 RED
 GREEN
 ORANGE
 BLUE

Shielded Multi-Conductor FT-4



Second Vendor		Third Vendor	
Second Vendor P/N		Third Vendor P/N	
Finished parts to be identified as per Engineering Instruction EI97-016.			
PARTS MUST BE FREE FROM LISTED PROHIBITED CHEMICAL SUBSTANCES STD 100-0002 AND STD 100-0003.			
NOTICE: This document is the exclusive property of Nova Bus, and may not be used or reproduced, nor its contents or part there of be disclosed to others by any person or company without the express consent in writing from Nova Bus.			
Written by	Date	Revised by	Date
J DUSSEAULT	2011-01-03	J DUSSEAULT	2011-01-13
Approved by	Date	Approved by	Date
C DESMARAIS	2011-03-01	C DESMARAIS	2011-01-13
Checked by	Date	Checked by	Date
Change description			
REV A - J DUSSEAULT 13/01/2011 DESCRIPTION CHANGED FROM "CABLE 6 PR X 20 AWG SHIELD" TO "CABLE 6 X 20 AWG SHIELD"			

FOR INTERNAL USE ONLY

REVISION

STATUS

DATE