



Specification Sheet

Lake Cable Part #: 206CS

Description: 20 AWG 6 conductor 7 strand bare copper wire with PVC insulation, shielded and overall PVC jacket for low-voltage electronic cable applications.

1. Conductor

- 1.1.AWG Size & Stranding: 20 AWG 7 Strands Class B
- 1.2.Material: Annealed Bare Copper
- 1.3.Conductor Count: 6 Conductors

2. Insulation

- 2.1.Material: Polyvinylchloride
- 2.2.Wall Thickness: 0.007"
- 2.3.Color Code: Black, Red, White, Green, Brown, Blue

3. Assembly

- 3.1.Nominal Lay Length: 2.25" LHL (5.33 Tw/Ft)
- 3.2.Shield: Aluminum Mylar - 100% Coverage
- 3.3.Drain Wire: 24 AWG 7 Strand Tinned Copper

4. Jacket

- 4.1.Material: Polyvinylchloride
- 4.2.Wall Thickness: 0.015"
- 4.3.Diameter: 0.185"
- 4.4.Color: Gray
- 4.5.Ripcord: Yes
- 4.6.Weight: 33 Lbs/Mft

5. Markings

- 5.1.Type: Cable permanently identified via surface inkjet print
- 5.2.Legend: LAKE CABLE E171197 20AWG 6C (UL) CMR C(UL)US OR (UL) CL3R
75°C SUN RES FT-4 "ROHS" MADE IN USA

5.3.Footage Markers: Yes

6. Standards

- 6.1.UL listed as type CL3R per UL standard 13 and as type CMR c(UL)us 75°C per UL standard 444
- 6.2.All materials used in the manufacture of this cable are RoHS compliant
- 6.3.Maximum Operating Voltage: 300V
- 6.4.Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of you order; this item may be non-cancelable and non-returnable.

Signature

Company

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION