

Mike: This is the 6 c 20 gauge



31390 VIKING PARKWAY
WESTLAKE, OH 44145

Dave Faga
Account Manager
Ext. 3206

Phone: (440) 250-2706
Toll Free: (888) 873-3206

Fax: (262) 957-5606
E-mail: davef@iewc.com

- 1) DESCRIPTION : 6 Cond. Foil & Braid CL2P CMP (B83606 ex. blk)
AWG 20/7x28 TC FEP/FEP Black
- 2) CONDUCTOR : AWG 20/7x28 Tinned Copper O.D.= .038"
- 3) INSULATION : FEP .007" wall O.D.= .050"-.054"
- 4) COLOR CODE : Black / Red / White / Green / Orange / Blue
- 5) TWIST LAY : 6" Lay on Cable
- 6) SHIELD : Aluminum / Mylar Shield with Aluminum side out
- 7) BRAID : Overall Tinned Copper Braid with 85% Coverage AWG 34
- 8) JACKET : Black FEP .015" wall O.D.= .218" nom.
- 9) MARKING : E111036 TYPE CL2P-E130356 TYPE CMP 20 AWG (UL), C(UL)
- 10) CAPACITANCE: n/a FEP/FEP
- 11) WEIGHT : 55 lbs / 1000 feet
- 12) TEMPERATURE: Operating -80C to 200C VOLTAGE: UL 300V Power Ltd.

Mike: This is the 6c 16 gauge



31390 VIKING PARKWAY
WESTLAKE, OH 44145

Dave Faga
Account Manager
Ext. 3206

Phone: (440) 250-2706
Toll Free: (888) 873-3206

Fax: (262) 957-5606
E-mail: davef@iewc.com

- 1) DESCRIPTION : 6 Conductors Foil & Braid CL2P CMP
AWG 16/19x.0117" TC FEP/FEP Black
- 2) CONDUCTOR : AWG 16/19x.0117" Tinned Copper O.D.= .057" nom.
- 3) INSULATION : FEP .007" Wall O.D.= .071"-.073"
- 4) COLOR CODE : Black / White / Red / Green / Orange / Blue
- 5) TWIST LAY : 6" Lay on Cable
- 6) SHIELD : Aluminum / Mylar Shield with Aluminum side out
- 7) BRAID : Overall Tinned Copper Braid with 85% Coverage AWG 34
- 8) JACKET : Black FEP .014" Wall O.D.= .276" nom.
- 9) MARKING : E111036 TYPE CL2P-E130356 TYPE CMP 16 AWG (UL), C(UL)
- 10) CAPACITANCE: 35 pf/feet FEP/FEP
- 11) WEIGHT : 85 lbs / 1000 feet
- 12) TEMPERATURE: Operating: -80C to 200C VOLTAGE: UL 300V Power Ltd.