

2006 P 96C



Product Data Sheet



Part Number: 92783A

Revision: 2/12/2014

3PR 20AWG PVC, UNSH, PVC

SOUND, ALARM AND SECURITY

A. CONSTRUCTION

Conductor: #20 AWG (7/28) Tinned Copper
 Insulation: .008" Wall, Plenum PVC
 Pair Assembly: 2 Conductors with a 2.00" LHL
 Cable Assembly: 3 Pairs with a 4.00" LHL
 Ripcord: Plenum Ripcord
 Jacket: .015" Wall, Plenum PVC
 Jacket Color: White (Munsell Centroid)
 Sequential Footage: Yes
 Print Legend: LOGISON(TM) / ACCUMASK (TM) - E50233-B 3 PAIR 20 AWG (UL) CL3P / (UL)C(UL) CMP 75C FT6 ROHS (date code - MM/YY) (sequential footage)

DIAMETERS

.036" Nom
 .052" Nom
 .104" Nom
 .180" Nom
 *.210" ± .012"

* Final OD to be verified during trial run

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL 444 / CSA C22.2 No. 214	Type CMP
National Electrical Code	Article 725
UL Standard 13	Type CL3P
Flame Compliances:	
NEC Type CMP, CL3P	NFPA 262
CEC Type CMP	CSA FT6

C. ELECTRICAL PROPERTIES

Temperature: 0°C to +75°C
 Suggested Working Voltage: 300 Vrms (Max)
 Conductor DCR: 10.9 Ohms/1000ft (Max) @ 20°C
 Capacitance (Cond-Cond): 31.8 pF/ft @ 1kHz (Nom)
 Characteristic Impedance: 61 Ohms @ 1MHz (Nom)

D. COLOR CODE

PAIR	COLOR 1	COLOR 2
1	BROWN	RED
2	BLACK	WHITE
3	BLUE	GREEN

E. CUSTOMER APPROVAL

Signature: _____

Date: _____

6/10/2014