

**ALPHA WIRE
CUSTOMER PRODUCT SPECIFICATION**

Part Number: IN1003042	Issue: 1
Page 1 of 2 Pages	Issue Date: 3/17/2010
	Effective Date: 3/17/2010

- A. Construction** **Diameters (In)**
- 1) Component 1 7 X 1 COND
 - a) Conductor 20 (10/30) AWG TC 0.037
 - b) Insulation 0.0325" Wall, Nom. PVC 0.102
 - (1) Color(s)

Cond	Color	Cond	Color	Cond	Color
1	WHITE	4	WHITE	7	BLACK
2	WHITE	5	WHITE		
3	WHITE	6	WHITE		

- 2) Cable Assembly 7 Components Cabled
- a) Twists: 3.4 Twists/foot (min)
- b) Core Wrap Nonwoven Polyester Tape, 25% Overlap, Min.
- 3) Shield: A/P/A Tape, 25% Overlap, Min.
- a) Drain Wire 20 (7/28) AWG TC
- b) Braid TC, 70% Coverage, Min.
- 4) Jacket 0.063" Wall, Nom., PVC 0.466 (0.489 Max.)
- a) Color(s) Slate, Black, Yellow, Orange, Blue, Green, Red, Sand Beige, White
- b) Ripcord 1 End 810 Denier Nylon
- c) Print ALPHA WIRE-* P/N IN1003042 7C 20 AWG

XTRAGUARD(R) 1 XTREME PERFORMANCE FOR XTREME ENVIRONMENTS (UL) MTW 600V OR AWM 2501 VW-1 -- LLXXXXXX CSA AWM IA/B IIA/B 105C 600 VOLTS FT4 CE ROHS (SEQ FOOTAGE)

* = Factory Code

[Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]

B. Industry Approvals

- 1) UL
 - a) Component 1 AWM/STYLE 1015 105°C / 600 V_{RMS}
 - MTW 90°C Dry / 60°C Wet / 600 V_{RMS}
 - b) Overall MTW 90°C Dry / 60°C Wet / 600 V_{RMS}
 - AWM/STYLE 2501 105°C / 600 V_{RMS}
 - VW-1
- 2) CSA International
 - a) Component 1 TEW 105°C / 600 V_{RMS}
 - b) Overall AWM I/II A/B 105°C / 600 V_{RMS}
 - FT4
- 3) CE: LVD 73/23/EEC Amendment 93/68/EEC

C. Environmental Approvals

- 1) EU Directive 2002/95/EC(RoHS): All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.
- 2) California Proposition 65: The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.

D. Physical & Mechanical Properties

- 1) Temperature Range -20 to 105°C
- 2) Bend Radius 10X Cable Diameter
- 3) Pull Tension 70 Lbs, Maximum
- 4) Sunlight Resistance Yes

E. Electrical Properties

- (For Engineering purposes only)
- 1) Voltage Rating 600 V_{RMS}
- 2) Capacitance 31 pf/ft @1 kHz, Nominal Conductor to Conductor
- 3) Ground Capacitance 56 pf/ft @1 kHz, Nominal

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

**ALPHA WIRE
CUSTOMER PRODUCT SPECIFICATION**

Part Number: IN1003042
Page 2 of 2 Pages

Issue: 1
Issue Date: 3/17/2010
Effective Date: 3/17/2010


- 4) Inductance 0.24 μ H/ft, Nominal
- 5) Conductor DCR 11.6 Ω /1000ft @20°C, Nominal
- 6) OA Shield DCR 2.12 Ω /1000ft @20°C, Nominal

F. Other

- 1) Packaging Flange x Traverse x Barrel (inches)
 - a) 1000 FT 24 x 14 x 12 Continuous length
 - b) 500 FT 18 x 12 x 8 Continuous length
 - c) 100 FT 12 x 10 x 5 Continuous length
 - d) Bulk(Made-to-order)

[Spool dimensions may vary slightly]

This Design is custom, Made-To-Order & once accepted, the order is NON-CANCELLABLE & NON-RETURNABLE.

Accepted By:  (SANDEEP MELOTH)	Date: 19 TH MARCH 2010
Company: HONEYWELL	Title: PROJECT LEADER

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.