



SPECIFICATION SHEET

Phone: 888- ELECTRO or 613-394-4896
Fax: 613-394-4101 email: sales@electrocables.com
Mailing: P.O. Box 276, Trenton, ON K8V 5R5
www.electrocables.com

26-Oct-2015

Product Number : **5152012TFT4**

RoHS

**Overall Shield Cable 12/C 20/7 AWG Stranded Tinned Copper
SR-PVC Insulation
PVC FT-4 Jacket**

Conductor : 20 AWG 7 Strand Tinned Copper Conductor	
Total Cable Weight : 104 kg/km	Final Diameter : 0.279 inches
Insulation : SR-PVC	DC Resistance 25°C: 10 Ohms / 1000 ft
Shield : Foil Shield 1.0	Mutual Capacitance : 29.2 pF/ft
Drain: 24 AWG 7 Strand Tinned Copper	Cond to Shield Cap. : 50.3 pF/ft
	Impedance : 60 Ohms
	Velocity of Prop : 65 %
	Inductance. : 1.4 mH/km
Outer Jacket : PVC	

Approvals : CSA AWG 600V 105°C CSA/UL CMG 300V 105°C

Print Notes :

Standard Print : ECI ELECTROCOM CSA CMG 105°C LL61365 OR CSA AWM II A/B 105°C
600V FT-4 (UL) CM E132883 105°C #20 AWG RoHS

Please contact Sales regarding Finished Lengths, Insulation and Jacket Colours.

All Cables are 100% Canadian Made in Ontario
Electro Cables Inc. has been manufacturing quality cables for over 30 years.
(All of the above values are approximated to within +/- 10%)

QMS Registered ISO 9001

5152012TFT4