



PRODUCT DATA SHEET

Controlled Document - Engineering Drive

1530 Shields Drive
 Waukegan, IL 60085
 Toll-Free (800) 323-9355
 Fax: (847) 689-1192

Construction Parameters: **Diameter**
 Component 1: 0.076
 Conductor: 20 AWG 26/34 Tinned Copper
 Insulation: EPDM-07 / Nom Wall: 0.02
 Color Code: Black, White, Red, Green, Orange, Blue, White/Black, Red/Black, Green/Black, Orange/Black, Blue/Black, Black/White ✓

Cabling: 12 Conductors cabled together (9 around 3) ✓
 Lay: 6.00" LHL

Jacketing:
 Outer Jacket Black CPE Nom Wall: 0.0525 ✓ 0.416
 Legend: 20 AWG 12C 300V SEACON ✓
 Print Color: White ✓
 Concentricity of Cable: Min. 50%- Measuring minimum wall thickness over maximum wall thickness **(FOR JACKET & INSULATION)**

Physical Properties:
 Temperature Range: 90°C ✓

Electrical Properties:
 Voltage Rating: 600 V RMS ✓

Industry Approvals: **Features:** **Compliance:**
 None RoHS: Complies with EU Dir. 2002/95/EC

Quote Number	No. Cond.	Gauge AWG/MCM	No. Strands	Nom. Cond.		Insulation Wall, Nom.		Jacket Wall, Nom.		G.D., Nom.		Net Weight	
				DCR Q/M'	Inches	mm	Inches	mm	Inches	mm	Lb./kft.	kg/km	
06219	12 ✓	20 ✓	26/34 ✓	11.20 ✓	0.020 ✓	0.51 ✓	0.053 ✓	1.33 ✓	0.416 ✓	10.57 ✓	105 ✓	157 ✓	

Note: All dimensions & weights are nominal subject to industry standards and tolerances unless otherwise noted.

Complies with EU Dir. 2002/95/EC
 The customer will accept all factory lengths and +/- 10 percent of total order requested.

The information presented here is, to the best of our knowledge, true and accurate. Since conditions of use are beyond Coleman Cable's control all product data presented is for informational purposes only and does not create a binding obligation or liability on Coleman Cable or confer any rights on any customer. The sale of products(s) is conditioned upon acceptance of a purchase order subject to Coleman disclaims all liability in connection with the use of information contained herein or otherwise.

This specification is proprietary intellectual property of Coleman Cable. Any information contained herein shall not be disclosed to any party without written consent of Coleman Cable.

Customer Company Name: SEACON GLOBAL

Date: 06/17/11

Customer Approval: [Signature]

Customer Title: Buyer

Specification Issue Date: 6/16/2011 Rev Level:

Designed By: GK