

**ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION**

Part Number: IN1001018	Issue: 1
Page 1 of 2 Pages	Issue Date: 1/7/2010
	Effective Date: 3/4/2010

- A. Construction** **Diameters (In)**
- 1) Component 1 17 X 1 COND
 - a) Conductor 20 (10/30) AWG TC 0.037
 - b) Insulation 0.0325" Wall, Nom. PVC 0.102
 - (1) Color(s)

Cond	Color	Cond	Color	Cond	Color
1	WHITE	7	WHITE	13	WHITE
2	WHITE	8	WHITE	14	WHITE
3	WHITE	9	WHITE	15	WHITE
4	WHITE	10	WHITE	16	WHITE
5	WHITE	11	WHITE	17	BLACK
6	WHITE	12	WHITE		

- 2) Cable Assembly 17 Components Cabled
 - a) Twists: 2.0 Twists/foot (min)
 - b) Core Wrap Nonwoven Polyester Tape, 25% Overlap, Min.
- 3) Shield: A/P/A Tape, 25% Overlap, Min.
 - a) Drain Wire 20 (7/28) AWG TC
 - b) Braid TC, 70% Coverage, Min.
- 4) Jacket 0.063" Wall, Nom., PVC 0.662 (0.694 Max.)
 - a) Color(s) Slate, Black, Yellow, Orange, Blue, Green, Red, Sand Beige, White
 - b) Ripcord 1 End 810 Denier Nylon
 - c) Print ALPHA WIRE-* P/N IN1001018 17C 20 AWG
XTRAGUARD(R) 1 XTREME PERFORMANCE FOR XTREME ENVIRONMENTS (UL) MTW 600V OR AWM 2501 VW-1 ---
LLXXXXXX CSA AWM I/A/B IIA/B 105C 600
VOLTS FT4 CE ROHS <SEQ FOOTAGE>

* = Factory Code
[Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]

B. Industry Approvals

- 1) UL
 - a) Component 1 AWM/STYLE 1015 105°C / 600 V_{RMS}
MTW 90°C Dry / 60°C Wet / 600 V_{RMS}
 - b) Overall MTW 90°C Dry / 60°C Wet / 600 V_{RMS}
AWM/STYLE 2501 105°C / 600 V_{RMS}
VW-1
- 2) CSA International
 - a) Component 1 TEW 105°C / 600 V_{RMS}
 - b) Overall AWM I/II A/B 105°C / 600 V_{RMS}
FT4
- 3) CE: LVD 73/23/EEC Amendment 93/68/EEC

C. Environmental Approvals

- 1) EU Directive 2002/95/EC(RoHS): All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.
- 2) California Proposition 65: The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.

D. Physical & Mechanical Properties

- 1) Temperature Range -20 to 105°C
- 2) Bend Radius 10X Cable Diameter
- 3) Pull Tension 151 Lbs, Maximum
- 4) Sunlight Resistance Yes

E. Electrical Properties

- 1) Voltage Rating (For Engineering purposes only) 600 V_{RMS}

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

**ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION**


Part Number: IN1001018 Page 2 of 2 Pages	Issue: 1 Issue Date: 1/7/2010 Effective Date: 3/4/2010
---	---

- 2) Capacitance 31 pf/ft @1 kHz, Nominal Conductor to Conductor
- 3) Ground Capacitance 56 pf/ft @1 kHz, Nominal
- 4) Inductance 0.24 μ H/ft, Nominal
- 5) Conductor DCR 11.6 Ω /1000ft @20°C, Nominal
- 6) OA Shield DCR 1.58 Ω /1000ft @20°C, Nominal

F. Other

- 1) Packaging
 - a) 1000 FT
 - b) 500 FT
 - c) 100 FT
 - d) Bulk(Made-to-order)

This Design is custom, Made-To-Order & once accepted, the order is NON-CANCELLABLE & NON-RETURNABLE.

Accepted By:  (SANDEEP P MELOTH)	Date: 19 TH MARCH 2010
Company: HONEYWELL	Title: PROJECT LEADER

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability. Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.