1. CONDUCTOR:

- 1.1 Size and Material: 20 AWG, stranding 19/32 AWG silver-plated copper wire.
- 1.2 O.D.: .038" nom.

2. INSULATION:

- 2.1 Extruded silicone rubber.
- 2.2 Covering: braided fiberglass yarn impregnated with a saturant to minimize fraying.
- 2.3 O.D.: .173" ± .005"
- 2.4 Color: white.

3. PERFORMANCE:

- 3.1 Voltage rating: 15 KVDC or 5 KVAC R.M.S.
 3.2 Temperature rating: -65^oC to 200^oC
- 3.3 Flame resistant per aviation certification requirements.

4. REFERENCES:

- 4.1 Same as Surprenant P/N SEHV(15)1932A(060)AGS.
- 4.2 Part number to order is shown in Description block.

CUSTOMER APPROVAL

Sign:	
Date:	

Engineering Change Notice No.					1			Done: Pièrre Garand			<u> </u>		
								Date:	May 7, 20		Harbour INDUSTRIES		
							This specification is the property of Harbour Industries Canada Limited and may not be used or	Verified:	Carit	115	Phone:	n	
			copied without the express written permission of Harbour Industries Canada Limited.	Date:		Description: XSR60S2019/32GB-9							
							ווו	May 7, 2008		X3R0032019/320B-9			
	A later revision of this specification may exist.				A member of The Marmon Group of companies	Size:	Scale:	^{Page:} 1 of 1	Code Ident. No: 57104	Specification No.: F01936-9	Rev.		