



CABLE TECHNOLOGY, INC.

73 RIVER ROAD - WILLINGTON, CT 06279 - (860) 429 - 7889 FAX (860) 429 - 3615

25C20-AMDWBS-DKGRAY

CONDUCTORS: #20 19/32 TC INSULATED WITH .010" SR PVC

CABLING: CABLE TWENTY-FIVE (25) CONDUCTORS TOGETHER

TAPE SHIELD: WRAP CORE WITH AN ALUMINUM/POLYESTER TAPE (FOIL FACING OUT)

DRAIN: #20 19/32 TC DRAIN WIRE (BETWEEN TAPE AND SHIELD)

SHIELD: TINNED COPPER BRAID 85% MIN. COVERAGE

JACKET: .041" DARK GRAY PVC

NOM OD: .453"

PRINT IN WHITE: E151405 20 AWG TYPE CM 75°C (UL)...VW-1...AWM 2464...LL52835 CSA (0675) AWM I/II A/B 80°C 300V FT-4...ROHS...CE

COLOR CODE:

1) BLACK	14) BROWN-WHITE
2) BROWN	15) RED-WHITE
3) RED	16) ORANGE-WHITE
4) ORANGE	17) GREEN-WHITE
5) YELLOW	18) BLUE-WHITE
6) GREEN	19) PURPLE-WHITE
7) BLUE	20) RED-BLACK
8) PURPLE	21) ORANGE-BLACK
9) GRAY	22) YELLOW-BLACK
10) WHITE	23) GREEN-BLACK
11) PINK	24) GRAY-BLACK
12) LT. GREEN	25) PINK-BLACK
13) BLACK-WHITE	

VOLTAGE RATING - 80°C
TEMP RATING - 300V
ROHS COMPLIANT

I HAVE REVIEWED ABOVE SPECIFICATION AND IT CONFORMS TO ITEM ORDERED UNDER PO#
NOTE AND EXCEPTIONS HERE →

SIGNED: _____ DATED: _____