

# Nickel Plated Brass Liquid Tight Strain Relief Fittings

## Multi-Hole - PG Threads



Nickel Plated Brass

Part Numbers		Thread Type & Size	Dimensions in Inches (mm)			Part Numbers of Inserts Only	
-40°F to 212°F (-40°C to 100°C)			No. of Holes	Diameter of Holes			
Dome	Flex**	See page 56 for thread specs		mm	Inches		
CD07AP-BR	CF07AP-BR		PG 7 / 1/4" NPT	Solid Insert			1.089.0799.19
CD09A1-BR	CF09A1-BR	PG 9	4	1.4	.06	1.089.0900.19	
CD09A2-BR	CF09A2-BR		2	3.0	.12	1.089.0901.19	
CD09A3-BR	CF09A3-BR		5	1.6	.06	1.089.0902.19	
CD09A4-BR	CF09A4-BR		2	1.7	.07	1.089.0903.19	
CD09A5-BR	CF09A5-BR		10	1.4	.06	1.089.0904.19	
CD09A6-BR	CF09A6-BR		6	1.4	.06	1.089.0905.19	
CD09A7-BR	CF09A7-BR		3	1.7	.07	1.089.0906.19	
CD09A8-BR	CF09A8-BR		4	1.7	.07	1.089.0907.19	
CD09A9-BR	CF09A9-BR		4	2.3	.09	1.089.0908.19	
CD09AP-BR	CF09AP-BR		Solid Insert			1.089.0999.19	
CD11A1-BR	CF11A1-BR		PG 11	2	3.0	.12	1.089.1100.19
CD11A2-BR	CF11A2-BR			3	3.0	.12	1.089.1101.19
CD11A3-BR	CF11A3-BR	2		4.0	.16	1.089.1102.19	
CD11A4-BR	CF11A4-BR	3		1.5	.06	1.089.1103.19	
CD11A5-BR	CF11A5-BR	4		2.8	.11	1.089.1104.19	
CD11AP-BR	CF11AP-BR	Solid Insert			1.089.1199.19		
CD13A1-BR	CF13A1-BR	PG 13 / 13.5	3	2.0	.08	1.089.1300.19	
CD13A2-BR	CF13A2-BR		6	3.0	.12	1.089.1301.19	
CD13A3-BR	CF13A3-BR		3	4.0	.16	1.089.1302.19	
CD13A4-BR	CF13A4-BR		2	5.0	.20	1.089.1303.19	
CD13A5-BR	CF13A5-BR		3	3.0	.12	1.089.1304.19	
CD13A6-BR	CF13A6-BR		2	5.2	.20	1.089.1305.19	
CD13A7-BR	CF13A7-BR		2	3.8	.15	1.089.1306.19	
CD13A8-BR	CF13A8-BR		2	4.2	.17	1.089.1307.19	
CD13A9-BR	CF13A9-BR		2	2.5	.10	1.089.1308.19	
CD13AP-BR	CF13AP-BR		Solid Insert			1.089.1399.19	
CD16A1-BR	CF16A1-BR	PG 16	3	3.0	.12	1.089.1600.19	
CD16A2-BR	CF16A2-BR		3	4.0	.16	1.089.1601.19	
CD16A3-BR	CF16A3-BR		4	4.0	.16	1.089.1602.19	
CD16A4-BR	CF16A4-BR		5	4.0	.16	1.089.1603.19	
CD16A5-BR	CF16A5-BR		6	4.0	.16	1.089.1604.19	
CD16A6-BR	CF16A6-BR		2	6.0	.24	1.089.1605.19	
CD16A7-BR	CF16A7-BR		3	5.6	.22	1.089.1606.19	
CD16A8-BR	CF16A8-BR		6	3.0	.12	1.089.1607.19	
CD16A9-BR	CF16A9-BR		*4	3.0	.12	*1.089.1610.19	
CD16A0-BR	CF16A0-BR		6	3.8	.15	1.089.1909.19	
CD16AP-BR	CF16AP-BR		Solid Insert			1.089.1699.19	

Part Numbers		Thread Type & Size	Dimensions in Inches (mm)			Part Numbers of Inserts Only	
-40°F to 212°F (-40°C to 100°C)			No. of Holes	Diameter of Holes			
Dome	Flex**	See page 56 for thread specs		mm	Inches		
CD21A1-BR	CF21A1-BR		PG 21	4	6.0		.24
CD21A2-BR	CF21A2-BR	3		7.0	.28	1.089.2101.19	
CD21A3-BR	CF21A3-BR	2		8.0	.31	1.089.2102.19	
CD21A4-BR	CF21A4-BR	4		5.0	.20	1.089.2103.19	
CD21A5-BR	CF21A5-BR	1		8.0	.31	1.089.2104.19	
CD21A6-BR	CF21A6-BR	4		5.2	.20	1.089.2105.19	
CD21A7-BR	CF21A7-BR	3		5.2	.20	1.089.2106.19	
CD21A8-BR	CF21A8-BR	4/1		5.2 / 3.7	.20 / .15	1.089.2107.19	
CD21A9-BR	CF21A9-BR	2		7.4	.29	1.089.2108.19	
CD21AP-BR	CF21AP-BR	Solid Insert			1.089.2199.19		
CD29A1-BR	-	PG 29		6	6.5	.26	1.089.2900.19
CD29A2-BR	-			4	9.0	.35	1.089.2901.19
CD29A3-BR	-		4	9.5	.37	1.089.2902.19	
CD29A9-BR	-		2	11.0	.43	1.089.2908.19	
CD29AP-BR	-		Solid Insert			1.089.2999.19	
CD36A1-BR	-	PG 36	5	9.0	.35	1.089.3600.19	
CD36A2-BR	-		7	9.0	.35	1.089.3601.19	
CD36A3-BR	-		6	8.0	.31	1.089.3602.19	
CD36A4-BR	-		2	15.0	.59	1.089.3603.19	
CD36AP-BR	-		Solid Insert			1.089.3699.19	
CD42A1-BR	-	PG 42	3	14.0	.55	1.089.4203.19	
CD42AP-BR	-		Solid Insert			1.089.4299.19	
CD48A1-BR	-	PG 48	8	10.0	.39	1.089.4800.19	
CD48A2-BR	-		6	12.0	.47	1.089.4801.19	
CD48A3-BR	-		3	18.0	.71	1.089.4802.19	
CD48AP-BR	-		Solid Insert			1.089.4899.19	

### RJ45 Solution

Part Numbers		Thread Type & Size	Dimensions in Inches (mm)		Part Numbers of Inserts Only
-40°F to 212°F (-40°C to 100°C)			Cable Diameter		
		See page 56 for thread specs	mm	Inches	
CD16AK-BR	PG 16		5.7	.23	
CD16AJ-BR	PG 16	6.9	.27	1.089.16C-07	

\*Note: RJ45 Solution has no approval ratings. Reference Diagram on page 24. For Strain Relief Fitting specifications and dimensions refer to page 14. For Material Specifications and Approval Information refer to page 52.

\*Note: This Insert has slotted holes.

\*\*Note: Flex Fittings are not a standard item, assembly required.

\*Note: CSA and CE Approvals only applies to Dome Fittings.



Optional Locking Nuts, O-Rings & Other Accessories starting on Page 29 - 40.

Dome Fittings also available with the following approvals:



ATEX

www.SealconEX.com

**Solid Plug can be customized!** Multi-Hole Inserts are available in Silicone and FKM upon request. "BP" (Billet Plugs) available.

