


DGC DATA GUIDE CABLE

SPECIALTY & CUSTOM CABLES

232 Sherman Street Gardner, MA 01440
 Phone: 978-632-0900 Fax: 978-630-1872
 Visit us on our website; www.dataquidecable.com



22 AWG 2 CONDUCTORS GRAY PVC/PVC 105C 300V

CONDUCTORS

(2 TOTAL):

- 22 AWG 7 Strands Tinned Annealed Copper in Accordance with ASTM B-3 and B-8

DIELECTRIC:

- .010" Nominal Wall Thickness PVC to Diameter of .050"

COLOR CODE:

- As Indicated


CABLE ASSEMBLY:

- Lay Length: 1-1/2" Nominal Left Hand Direction
 - Filler: Polypropylene

JACKET:

- Material: Thermoplastic 105C PVC
 - Color: Gray
 - Wall Thickness: .032" Nominal
 - Separator: .002" Tissue
 - Finished Cable Diameter: .170" +/- .005"

CABLE IDENTIFICATION:

- TYPE: Surface Print on Jacket
 - Ink Color: Black
 - Legend: E90298  AWM 2517 105C 300V VW1 -- LL91737 CSA AWM I/II A/B 105C 300V FT1"

COLOR CODE

CONDUCTOR	COLOR
1	WHITE
2	WHITE

LISTINGS/AGENCY APPROVAL

- UL AWM 2517 105C 300VOLTS
 - CSA AWM FT1 105C 300VOLTS

REVISION HISTORY

0	3/29/10	WJD	INITIAL RELEASE
1	3/12/18	WJD	REFORMAT RE-RELEASE

Customer Number	
D.G. Part Number	10D1-6
Prepared By: LLJ	
Reviewed By: WJD	