



US North Central
 5001 S. Towne Drive
 New Berlin, WI 53151
 800-344-2323
www.IEWC.com

Specification

Issue Date: 4/24/2013

Issue: 1

Construction

Description:	2 Cond 22 (7/30) TC PVC-PVC Canfield W1000				Diam. (In)	
Component:	2 Conductors					
Conductor:	22 7/30 TC to ASTM B 33-74				0.03"	
Insulation:	0.017" Premium Grade PVC				0.064"	
Color Code:						
	<i>Cond</i>	Color	<i>Cond</i>	Color	<i>Cond</i>	Color
	1	Black	2	Red		
Cable Assembly:	2 Conductors Bunched Cabled				0.128"	
Jacket:	0.036"	GFE8085 Jacket Compound			0.200"	
Jacket Color:	Black	GRAY			0.200"	
Print:	E174416 RU AWM-2464 80C 300V VW-1 ----cRU AWM I/II A 80C 300V FT1 CANFIELD CONNECTOR (Royal Blue) W1000 22/2					
Specifications:						
UL	AWM - 2464	80°C	300 Volt	VW-1		
Canadian cUR	AWM	80°C	300 Volt	FT-1		
THE BENDING RADIUS SHOULD BE 8 TIMES <u>OR LESS</u> THE CABLE'S OUTSIDE DIAMETER. BENDING RADIUS = 1.6 INCHES						
Wire must be free stripping, talc at jacket to promote stripability						
Environmental Compliance						
EU Directive 2002/95/EC(RoHS): All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment.						
REACH Regulation (EC 1907/2006): This product does not contain Substances of Very High Concern (SVHC) listed on the European Union's REACH candidate list in excess of 0.1% mass of the item.						
California Prop 65: The outer surface materials used in the manufacture of this part meet the requirements of California Prop. 65.						

Outer Jacket needs to be GRAY!!

APPROVED

MSP 4/26/2013