


Multi-Conductor - Unshielded

Multi-Conductor - Unshielded CSA - FT-4 - UL



Stranded Tinned Copper Conductors
Conductors Twisted
SR PVC Insulation
PVC Jacket - Grey
-20° C + 105° C

9222W, 9184W, 9182W - White Jacket
9162BK, 9142BK - Black Jacket

Cat. No.	No. Cond.	Cond. Size	Cond. Strand	Insul. Thick	Jkt. Thick	Nom D.D.	Voltage	Put-Up meters	Weight lbs.	Colour Code
9222	2	22	7x30	.010	.015	.131	600	300/150	12/6	Blk/Red
9222W	2	22	7x30	.010	.015	.131	600	300/150	12/6	Blk/Red
9223	3	22	7x30	.010	.015	.139	600	300/150	14/7	Blk/Red/Gr.
9224	4	22	7x30	.010	.015	.152	600	300/150	18/9	1
9225	5	22	7x30	.010	.015	.160	600	300/150	22/11	1
9226	6	22	7x30	.010	.023	.192	600	300/150	32/16	1
9227	7	22	7x30	.010	.023	.203	600	300/150	34/17	1
9228	8	22	7x30	.010	.023	.215	600	300/150	38/19	1
9229	9	22	7x30	.010	.023	.225	600	300/150	42/21	1
9210	10	22	7x30	.010	.023	.234	600	300/150	46/23	1
9212	12	22	7x30	.010	.023	.251	600	300/150	54/27	1
9215	15	22	7x30	.010	.023	.275	600	300/150	64/32	2
9216	16	22	7x30	.010	.023	.285	600	300/150	68/34	2
9220	20	22	7x30	.010	.030	.323	600	300/150	86/43	2
9325	25	22	7x30	.010	.030	.354	600	300/150	104/52	2
9330	30	22	7x30	.010	.030	.381	600	300/150	124/62	2
9340	40	22	7x30	.010	.030	.432	600	300/150	158/79	2
9350	50	22	7x30	.010	.030	.483	600	300/150	194/97	2
9202	2	20	7x28	.010	.015	.146	600	300/150	14/7	Blk/Red
9203	3	20	7x28	.010	.015	.154	600	300/150	18/9	Blk/Red/Gr
9204	4	20	7x28	.010	.023	.189	600	300/150	30/15	1
9205	5	20	7x28	.010	.023	.197	600	300/150	34/17	1
9207	7	20	7x28	.010	.023	.225	600	300/150	46/23	1
9209	9	20	7x28	.010	.023	.249	600	300/150	56/28	1
9012	12	20	7x28	.010	.023	.279	600	300/150	70/35	1
9015	15	20	7x28	.010	.030	.306	600	300/150	84/42	2
9019	19	20	7x28	.010	.030	.338	600	300/150	106/53	2
9025	25	20	7x28	.010	.030	.380	600	300/150	132/66	2
9182	2	18	16x30	.012	.023	.195	600	300/150	26/13	Blk/Red
9182W	2	18	16x30	.012	.023	.195	600	300/150	26/13	Blk/Red
9183	3	18	16x30	.012	.023	.207	600	300/150	34/17	Blk/Red/Gr
9184	4	18	16x30	.012	.023	.226	600	300/150	44/22	1
9184W	4	18	16x30	.012	.023	.226	600	300/150	44/22	1
9185	5	18	16x30	.012	.023	.237	600	300/150	50/25	1
9186	6	18	16x30	.012	.023	.255	600	300/150	58/29	1
9187	7	18	16x30	.012	.023	.271	600	300/150	66/33	1
9188	8	18	16x30	.012	.023	.286	600	300/150	74/37	1
9189	9	18	16x30	.012	.023	.300	600	300/150	82/41	1
9812	12	18	16x30	.012	.030	.353	600	300/150	108/54	2
9815	15	18	16x30	.012	.030	.386	600	300/150	132/66	2
9819	19	18	16x30	.012	.030	.429	600	300/150	164/82	2