



Aerospace Part#: 1288/19w **CONTROL CABLE** 

# **DESCRIPTION**

2 Conductors AWG 22/19x34 TC Overall Braid Shield FEP/FEP White 200C 600V

### **PHYSICAL PROPERTIES**

**Conductors** Insulation

# Conductors	AWG	Material	Material	Wall	Finished OD
2	22/19x34	Tinned Copper	FEP	.010"	.050"

### **Outer Braid Material**

Layer 1 Type	Material	AWG	Coverage
Overall Braid Shield	Tinned Copper	36	85%

**Outer Jacket Material** Cabling

Jacket Material	Color	Wall	Overall O.D.	Lay
FEP	White	.015"	.153" Nom.	2" Lay on Cable with Clear Mylar

#### **MECHANICAL PROPERTIES**

Operating Temp	Total Weight	Bend Radius
Rated -80C to 200C	20.9 lbs/m	10 X OD

#### **ELECTRICAL PROPERTIES**

<u>EEEGTRIOAET ROTERTIEG</u>	
Max. Operating Voltage	
Rated 600 Volts	

### **INDUSTRY APPROVALS AND COMPLIANCE**

#### Standarde & Environmental Programs

Standards & Environmental Programs	
Reach / RoHS Compliant	YES
Suitability	Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasian, Acid

# **MISCELLANEOUS**

Color Black / White /

Code:

# **Contact Us For More Information**

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

<sup>\*</sup> Specification subject to error and may change without notice