

## 6500FE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled



For more Information  
please call

1-800-Belden1



### General Description:

Security & Commercial Audio Cable, Plenum-CMP, 2-22 AWG stranded bare copper conductors with Flamarrest® insulation, Beldfoil® shield and Flamarrest® jacket with ripcord

### Usage (Overall)

Suitable Applications: Intercom/PA Systems and Sound/Audio Systems

### Physical Characteristics (Overall)

#### Conductor

AWG:

# Conductors	AWG	Stranding	Conductor Material
2	22	7x30	BC - Bare Copper

Total Number of Conductors: 2

#### Insulation

Insulation Material:

Insulation Trade Name	Insulation Material	Wall Thickness (in.)
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	0.009

#### Outer Shield

Outer Shield Material:

Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape w/Shorting Fold	100

Outer Shield Drain Wire AWG:

AWG	Stranding	Drain Wire Conductor Material
24	7x32	TC - Tinned Copper

#### Outer Jacket

Outer Jacket Material:

Outer Jacket Trade Name	Outer Jacket Material	Nom. Wall Thickness (in.)
Flamarrest®	LS PVC - Low Smoke Polyvinyl Chloride	.015

Outer Jacket Ripcord: Yes

### Overall Cable

Overall Cabling Lay Length & Direction:

Length (in.)	Twists (twist/ft)
2.5	4.8

Overall Cabling Color Code Chart:

Number	Color
1	Black
2	Red

Overall Nominal Diameter: 0.128 in.

### Mechanical Characteristics (Overall)

Operating Temperature Range: 0°C To +75°C

UL Temperature Rating: 75°C

Bulk Cable Weight: 11.300 lbs/1000 ft.

Max. Recommended Pulling Tension: 24 lbs.

Min. Bend Radius/Minor Axis: 1.300 in.

### Applicable Specifications and Agency Compliance (Overall)

#### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMP

NEC Articles: 800

## 6500FE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled

CEC/C(UL) Specification:	CMP
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

### Flame Test

UL Flame Test:	NFPA 262
C(UL) Flame Test:	FT6

### Suitability

Suitability - Indoor:	Yes
-----------------------	-----

### Plenum/Non-Plenum

Plenum (Y/N):	Yes
Non-Plenum Number:	5500FE

## Electrical Characteristics (Overall)

### Nom. Inductance:

Inductance (µH/ft)
.17

### Nom. Capacitance Conductor to Conductor:

Capacitance (pF/ft)
55

### Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/ft)
99

### Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
16.4

### Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
15.3

### Max. Operating Voltage - UL:

Voltage
300 V RMS

### Max. Recommended Current:

Description	Current
10C Temperature Rise	2.8 Amps per conductor @ 25°C ambient

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
6500FE 003U1000	1,000 FT	13.000 LB	ORANGE		2 #22 FLRST FS FLRST
6500FE 0031000	1,000 FT	12.000 LB	ORANGE		2 #22 FLRST FS FLRST
6500FE 008U1000	1,000 FT	12.000 LB	GRAY		2 #22 FLRST FS FLRST
6500FE 009U1000	1,000 FT	12.000 LB	WHITE		2 #22 FLRST FS FLRST
6500FE 009U250	250 FT	3.750 LB	WHITE		2 #22 FLRST FS FLRST
6500FE 010U1000	1,000 FT	12.000 LB	BLACK		2 #22 FLRST FS FLRST
6500FE 010U250	250 FT	3.750 LB	BLACK		2 #22 FLRST FS FLRST
6500FE 010U500	500 FT	6.500 LB	BLACK		2 #22 FLRST FS FLRST
6500FE 877C500	500 FT	5.500 LB	NATURAL		2 #22 FLRST FS FLRST
6500FE 877U1000	1,000 FT	12.000 LB	NATURAL		2 #22 FLRST FS FLRST
6500FE 877U250	250 FT	3.750 LB	NATURAL		2 #22 FLRST FS FLRST
6500FE 877U500	500 FT	6.500 LB	NATURAL		2 #22 FLRST FS FLRST
6500FE 8771000	1,000 FT	12.000 LB	NATURAL	C	2 #22 FLRST FS FLRST
6500FE 877500	500 FT	6.000 LB	NATURAL		2 #22 FLRST FS FLRST

Notes:

## 6500FE Multi-Conductor - Commercial Audio Systems - 2 Conductors Cabled

C = CRATE REEL PUT-UP.

Revision Number: 3    Revision Date: 03-19-2015

© 2015 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.