



Specification Sheet

COMPANY: INDUSTRIAL ELECTRIC WIRE & CABLE

DATE: 09/20/07

TWC PART NUMBER: P21015.1/2280AB2M/CMP/CL3P

CONSTRUCTION : 22AWG 7/0096 BARE COPPER
2 CONDUCTORS OVERALL FOIL

COLOR CODE : CC#296: YELLOW, YELLOW

INSULATION : 0.007 Inch, Low Smoke PVC

SHIELD/DRAIN : ALUM/POLY FOIL 100% COV. 24AWG 7/32 TC. DW.

CAPACITANCE : 42.6 pF/ft Nom.

VEL OF PROP : 55%

IMPEDANCE : 43 OHMS

RESISTANCE : 17.5 OHMS D.C. PER 1000 FT @ 68 DEG. F

TEMP/VOLTAGE : 75 DEGREES C

JACKET : YELLOW, 0.015 Inch, LOW SMOKE PVC -- 0.116 Nom OD

CABLE WT : 10.25 Lb/1000Ft Approx (EXCLUDING REEL OR BOX)

PRINT LEGEND : 10K-2 E118871 CMP/CL3P/FPLP 22AWG (UL) C(UL) 75C FT6 MADE
IN USA "ROHS COMPLIANT"

UL : CMP/CL3P

MISC : MADE IN USA

* +/- 10% Manufacturing tolerance

* On non-standard product, customer agrees to accept all lengths manufactured

APPROVED BY