



Specification Sheet

TWC PART NUMBER: L20015.2/2280AT2M/CM/CL3

CONSTRUCTION : 22AWG 7/0096 TINNED COPPER 2 CONDUCTORS OVERALL FOIL
COLOR CODE : CC#6: BLACK,CLEAR
INSULATION : 0.016 Inch, LDPE
SHIELD/DRAIN : OVERALL FOIL SHIELD, FOIL-OUT (BLUE IN). 24AWG 7/32 TC. DW
CAPACITANCE : 19 pF/ft Nom.
VEL OF PROP : 66.2%
IMPEDANCE : 81 OHMS
RESISTANCE : 17.5 OHMS D.C. PER 1000 FT @ 68 DEG. F
JACKET : YELLOW, 0.025 Inch, PVC -- 0.172 Nom OD
CABLE WT : 16.4 Lb/1000Ft Approx (EXCLUDING REEL OR BOX)
PRINT LEGEND : NOVAR BUILDING MANAGEMENT SYSTEMS OUTDOOR LIGHT SENSOR
E118871 CM/CL3 22AWG (UL) c(UL) CMH MADE IN USA RoHS
COMPLIANT
UL : CM/CL3
MISC : MADE IN USA

* +/- 10% Manufacturing tolerance

* On non-standard product, customer agrees to accept all lengths manufactured

APPROVED BY

Tappan Wire & Cable Inc. provides information and specifications on an "as is" basis. Information in specifications described herein are subject to error and/or omission, and subject to change without notice. Although we make all efforts possible to ensure the accuracy and timeliness of the information, Tappan Wire & Cable, will not be held liable for any damages whatsoever, even if advised of the possibility of such damages, arising from the use, or inability to use, the information or specifications herein. Please refer to our "Website Use Policy", listed on our website, www.tappanwire.com, under the Sales Support Section for full details, or contact your Tappan Representative. This drawing may contain patented or proprietary information. It is the property of Tappan Wire and must not be used in any way detrimental to Tappan Wire. Acceptance by signature of this drawing will be considered as an agreement of and acceptance of the foregoing.