



Deca Cables Inc.
 150 North Murray Street
 P.O. Box 777
 Trenton, Ontario K8V 5W6
 Canada

Website: www.decacables.com
 Telephone: (613) 392-3585
 Facsimile: (613) 392-7908
 Email: sales@decacables.com

ISO 9001:2008

PRODUCT DATA SHEET

Part No: 73-342

CONSTRUCTION SPECIFICATIONS

Description	AWM 2C 22 AWG Shielded
Conductor	22 AWG 7 Strand Tinned Copper - Concentric
Conductor Diameter	0.030"
Insulation Type	Semi Rigid PVC
Insulation Thickness	0.008"
Cable Assembly	Conductors are cabled together with an overall shield and drain wire. (foil out, drain out)
Drain Wire	24 AWG 7 Strand Tinned Copper - Concentric
Overall Shielding Tape	Aluminum/mylar
Ripcord	Polyester Ripcord included under the cable jacket
Jacket	Flame Retardant PVC
Jacket Thickness	0.030" (minimum average)
Overall Cable Diameter	0.162"
Jacket Print	CSA AWM II A/B105C 600V FT4 LL67097 CMG 22 AWG 60C LL83251 RU AWM STYLE 2464 80C 300V E111002 ROHS (work order)

ELECTRICALS

Voltage	300V; CMG, AWM STYLE 2464 / 600V; AWM II
Conductor Resistance	16.6 Ohms/Mft @20C

CERTIFICATIONS AND PHYSICAL PROPERTIES

CSA Certified	*CSA C22.2 No. 214, Communications Cables *CSA C22.2 No. 210.2, Appliance Wiring Material Products
UL Recognized	*UL 758, Appliance Wiring Material
Flame Test Rating	CSA FT4
Temperature Rating	60C; CMG, / 105C; AWM II / 80C; AWM STYLE 2464
ROHS	Compliant
Cable Weight	22.6 kg/km
Copper Content	7.74 kg/km
Max Pull Tension	7 kgs
Min Bending Radius	2.00 inches (installed)
Min Installation Temp	-20C

Rev. 000

11-Apr-13