



**GENERAL PRODUCT SPECIFICATION**  
 Phone 800-316-8877 Fax 978-368-1275  
 www.jamesmonroewire.com

**Description:** Two Conductor, 22 AWG  
 Overall Foil Shield and PVC Jacket

**Date:** 7/29/2014

**JM Part Number:** JM57274  
**Reference:** 2202COFS-8JM3

<u>Components</u>	
Two 22 AWG Insulated Conductors	
Conductor:	22 AWG, 7/30 tinned copper
Insulation:	.010" nominal wall of Semi-Rigid PVC (see color code) .050"

<u>Cable Construction</u>	
Cabling:	Two insulated conductors twisted together, No Filler
Shield:	Aluminum-Mylar tape, Aluminum side OUT
Drain Wire:	22 AWG, 7/30 tinned copper
Jacket:	.032" nominal wall of Gray PVC .168" (± .008")

<u>Color Code</u>	
1. Black	2. Red

Surface Print - Inkjet  
 E138031 2/C 22 AWG 75C SHIELDED (UL) TYPE CM OR AWM 2576 80C 150V VW-1  
 --- LL41103 CSA TYPE CMG 60C FT4 --- CE ROHS

<u>Requirements</u>			
Temperature:	80C	Approvals:	UL Type CM
Voltage:	150V		AWM Style 2576
			CSA Type CMG
			CE-LVD & RoHS Compliant (2011/65/EU)

Written By:	rjc	7/29/2014	Rev. 0	Initial
Revised By:	scs	8/5/2014	Rev. 1	Added JM and Reference Numbers
Revised By:				
Revised By:				