

SPECIFICATION SHEET  
=====

PRODUCT #5152202 FT-4

DATE :  
Sep-95

PRODUCT DESCRIPTION  
-----

AUDIO 24/7  
STR STD 0.010 SR INS SHLD 24/7 DRAIN  
0.015 PVC JKT FT-4 105C 600V  
0.020

92214

CONDUCTOR		# 22 AWG TINNED COPPER
STRANDING		7 X .010
CONDUCTOR RESISTANCE (ohms/Mft)		14.86
CONDUCTOR CMA		700
INSULATING MATERIAL		SEMI-RIGID PVC FT-4
SPECIFIC GRAVITY		1.39
WALL THICKNESS (INCHES)		0.010
CONDUCTOR INSULATED O.D. (INCHES)		0.050
CABLING LAY (INCHES)		1.50
OVERALL DRAIN WIRE SIZE		# 24 AWG TINNED COPPER
FINAL TWISTED O.D. (INCHES)		0.102
JACKET THICKNESS (INCHES)		0.015
JACKET TYPE		FT-4 PVC JKT GREY
SPECIFIC GRAVITY		1.36
FINISHED CABLE O.D. (INCHES)		0.142
COPPER CONTENT (KGS/KM)		8.932
TOTAL CABLE WEIGHT (KGS/KM)		16.754
CSA APPROVED		YES
UL APPROVED		YES
VELOCITY OF PROPAGATION %		47%
CHAR. IMPEDANCE (ohms) within 10%		<del>75</del>
CAPACITANCE (pF/ft) within 10%		<del>35</del>

NOTE: This cable meets the specifications listed but is not AES/EBU approved.