



Specification Sheet

Lake Cable Part #: 222CST-DEL

Description: 22 AWG 2 conductor 7 strand tinned copper wire with PVC insulation, shielded, and PVC jacket for low-voltage electronic cable applications

1. Conductor

- 1.1.AWG Size & Stranding: 22 AWG 7 Strands Class B
- 1.2.Material: Annealed Tinned Copper
- 1.3.Conductor Count: 2 Conductors

2. Insulation

- 2.1.Material: Polyvinylchloride
- 2.2.Wall Thickness: 0.010"
- 2.3.Color Code: Black, Red

3. Assembly

- 3.1.Nominal Lay Length: 2.00" LHL (6.00 Tw/Ft)
- 3.2.Shield: Aluminum/Mylar - 100% Coverage
- 3.3.Drain Wire: 24AWG 7 Strands Tinned Copper

4. Jacket

- 4.1.Material: Polyvinylchloride
- 4.2.Wall Thickness: 0.015"
- 4.3.Diameter: 0.129"
- 4.4.Color: Gray
- 4.5.Ripcord: Yes
- 4.6.Weight: 13 Lbs/Mft

5. Markings

- 5.1.Type: Cable permanently identified via surface inkjet print
- 5.2.Legend: DELCO 33632 E171197 22AWG 2C SHLD (UL) CMG C(UL)US OR (UL) CL3R 75°C
SUN RES FT-4 "ROHS" MADE IN USA
- 5.3.Footage Markers: Yes

6. Standards

- 6.1.UL listed as type CL3R per UL standard 13 and as type CMG c(UL)us 75°C per UL standard 444
- 6.2.All materials used in the manufacture of this cable are RoHS compliant
- 6.3.Recommended Operating Voltage: 300V
- 6.4.Made in the USA

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION