




MULTI-CONDUCTOR CABLE

TINNED COPPER SHIELDED

SHIELDED MICROPHONE CABLE



APPLICATIONS:
 All high impedance microphones - lapel, ribbon, velocity, crystal contact, static, intercom, public address cables. All low impedance microphones - carbon, condenser, dynamic.

OLYMPIC NO.	NO. OF COND.	CONDUCTOR SIZE	STRAND	NOM. WALL THICK.	NOM. JACKET THICK.	NOM. O.D.	SUGG. WORK VOLT.	COLOR CODE
-------------	--------------	----------------	--------	------------------	--------------------	-----------	------------------	------------

DESCRIPTION:

Tinned copper, polyethylene insulation, tinned copper spiral wrap shield, chrome vinyl jacket. Temp. Rating -20°C to +60°C CL2

Tinned copper, polyethylene insulated, conductors cabled, tinned copper braid shield, chrome vinyl jacket. Temp. Rating -20°C to +60°C CL2

Tinned copper, polyethylene insulation, braided tinned copper shield, gray vinyl jacket. Temp. Rating -20°C to +60°C

Tinned copper conductor, color coded rubber insulation, tinned copper braid shield, black rubber jacket. Temp. Rating -20°C to +60°C

6805	1	26	3/34 4/34*	.016"	.020"	.110"	1000	Blk
6806	2	22	19/34	.025"	.025"	.230"	1000	Blk, Whit
3005	2	20	26/34	.015"	.030"	.245"	600	Blk, Whit
3500	2	20	26/34	.020"	.035"	.260"	600	Blk, Whit,
3501	3	20	26/34	.020"	.035"	.275"	600	Red

* 3 str. tinned copper ; 4 str. tinned copper weld.

SPIRAL SHIELDED VINYL JACKETED CABLE

UL CLASSIFIED CL2 or CM



OLYMPIC NO.	UL STYLE NUMBER	NO. OF COND.	CONDUCTOR SIZE	STRAND	NOM. WALL THICK.	NOM. JACKET THICK.	NOM. O.D.	SUGG. WORK VOLT.
-------------	-----------------	--------------	----------------	--------	------------------	--------------------	-----------	------------------

DESCRIPTION:

Tinned copper, vinyl insulation, conductors twisted, 95% spiral wrapped, tinned copper shield, chrome vinyl jacket. Temp. Rating -20°C to +80°C

COLOR CODE:

- 1 - Black
- 2 - Red
- 3 - White
- 4 - Green
- 5 - Yellow
- 6 - Blue

+2895	2095 (300v)	2	22	Solid	.015"	.025"	.160"	350
+2897	1108 (300v)	1	22	7/30	.016"	.020"	.115"	350
2896	2095 (300v)	2	22	7/30	.015"	.025"	.170"	350
+2898	2095 (300v)	3	22	7/30	.016"	.020"	.190"	350
+2899	2095 (300v)	4	22	7/30	.016"	.020"	.200"	350
+2900	2095 (300v)	6	22	7/30	.016"	.020"	.235"	350
+2901	1108 (300v)	1	20	10/30	.016"	.020"	.130"	350
2902	2095 (300v)	2	20	7/28	.015"	.025"	.199"	350
+2903	2095 (300v)	3	20	10/30	.016"	.020"	.210"	350
+2904	2095 (300v)	4	20	10/30	.016"	.020"	.225"	350
+2905	2095 (300v)	6	20	10/30	.016"	.020"	.265"	350
+2906	1108 (300v)	1	18	16/30	.016"	.020"	.135"	350
*2907	2095 (300v)	2	18	7/26	.020"	.028"	.241"	450
+2908	2095 (300v)	3	18	7/26	.016"	.020"	.230"	450
+2909	2095 (300v)	4	18	16/30	.016"	.020"	.245"	350
**2910	2095 (300v)	2	16	19/29	.023"	.030"	.266"	450

† Bare copper spiral shield *Red/White **Black/White

Passes the VW-1 vertical flame test