

Aerospace Part#: 1288spcdu

CONTROL CABLE

DESCRIPTION

2 Conductors AWG 22/19x34 TC
Overall SPC Braid Shield FEP/FEP White

PHYSICAL PROPERTIES

Conductors

Insulation

# Conductors	AWG	Material	Material	Wall	Finished OD
2	22/19x34	Silver Plated Copper	FEP	.010"	.050"

Outer Braid Material

Drain Wire

Layer Type	Material	AWG	Coverage	AWG	Material
Each Conductor Braid Shield	Silver Plated Copper	38	95%	20/19x32	Silver Plated Copper

Outer Jacket Material

Cabling

Jacket Material	Color	Wall	Overall O.D.	Lay
FEP	White	.010"	.138" x .118" Nom.	Parallel

MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius
Rated -80C to 200C	23 lbs / m	10 X OD

ELECTRICAL PROPERTIES

Max. Operating Voltage	Capacitance (Cond. To Drain)
300 Volt	55 pf / ft nom.

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

Reach / RoHS Compliant	YES
Suitability	Indoor, Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasion, Acid

MISCELLANEOUS

Color Code: Black / Clear /

Contact Us For More Information

T: 800.395.0200 **F:** 718.358.2522 **E:** sales@aerospacewire.com **W:** www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

* Specification subject to error and may change without notice