



**GENESIS SERIES**

**Low Voltage Cable  
Part No. 3252**

Description: 22 AWG 1PR STR CMP-CL2P Level 4  
Specifications: UL Standards 13 & 444; NEC Articles 725 & 800

**Construction:**

Conductor 22 AWG 7/0.096 Bare Copper  
Insulation FEP  
Insulation Thickness 0.008" nom.  
Insulation Colors Blu, Wht/blu  
Insulation Diameter 0.045 nom.  
Lay Length 1.5" max.

Jacket Plenum PVC  
Jacket Color Natural  
Jacket Thickness 0.015" nom.  
Cable Diameter 0.124" nom.  
Legend (Ink Print)

**HONEYWELL LEVEL 4 1PR22 3038058 (ETL) CL2P OR CMP C(ETL)US FT6  
W/O XXXXXX-XXXXXX FT#XXXXXX RM# A B C D E F 1 2 3 4 5 6 7 8 9 FOR USE IN  
LONWORKS NETWORKS**

**Properties:**

Temperature Rating -20 to 75 °C  
Operating Voltage 300 Volts max.  
Capacitance 14.5 pf/ft nom.  
Impedance 100 Ohms nom.  
DC Resistance 16.5 Ohms/M' at 20°C  
Flame Rating UL 910, NFPA 262, CSA FT6