

**Aerospace Part#:** TBD

**CONTROL CABLE**

**DESCRIPTION**

1 Pair AWG 22/7x30 SPC  
Overall Foil & Braid Shield PTFE/FEP Black 600V

**PHYSICAL PROPERTIES**

Pairs			Insulation		
# Pairs	AWG	Material	Material	Wall	Finished OD
1	22/7x30	Silver Plated Copper	PTFE	.010"	.050"

Outer Shield Material			Drain Wire	
Shield Type	Material	Coverage	AWG	Material
Overall Foil Shield	Alum / Mylar	100%	24/7x32	Silver Plated Copper

Outer Braid Material			
Layer 1 Type	Material	AWG	Coverage
Overall Braid Shield	Silver Plated Copper	36	85%

Outer Jacket Material			Cabling	
Jacket Material	Color	Wall	Overall O.D.	Lay
FEP	Black	.015"	.157" Nom.	1" Lay on Cable

**MECHANICAL PROPERTIES**

Operating Temp	Total Weight	Bend Radius
Rated -65C to 200C	24.0 lbs/m	10 X OD

**ELECTRICAL PROPERTIES**

Max. Operating Voltage
Rated 600 Volts

**INDUSTRY APPROVALS AND COMPLIANCE**

Standards & Environmental Programs	
RoHS Compliant	YES
Suitability	Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasion, Acid

**MISCELLANEOUS**

Color: Black / Red /  
Code:

[Contact Us For More Information](#)

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

**LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA**

\* Specification subject to error and may change without notice