

**Aerospace Part#:** TBD

**CONTROL CABLE**

**DESCRIPTION**

1 Pair AWG 22/7x30 SPC  
Overall Foil Shield PTFE/FEP Black 600V

**PHYSICAL PROPERTIES**

**Pairs**

**Insulation**

# Pairs	AWG	Material	Material	Wall	Finished OD
1	22/7x30	Silver Plated Copper	PTFE	.010"	.050"

**Outer Shield Material**

**Drain Wire**

Shield Type	Material	Coverage	AWG	Material
Overall Foil Shield	Alum / Mylar	100%	22/7x30	Silver Plated Copper

**Outer Jacket Material**

**Cabling**

Jacket Material	Color	Wall	Overall O.D.	Lay
FEP	Black	.015"	.134" Nom.	1" Lay on Cable

**MECHANICAL PROPERTIES**

Operating Temp	Total Weight	Bend Radius
Rated -65C to 200C	16 lbs/m	10 X OD

**ELECTRICAL PROPERTIES**

Max. Operating Voltage
Rated 600 Volts

**INDUSTRY APPROVALS AND COMPLIANCE**

**Standards & Environmental Programs**

RoHS Compliant	YES
Suitability	Direct Burial, Wet Location
Resistance	Oil, Gas, Sunlight, Abrasion, Acid

**MISCELLANEOUS**

Color Red / White /  
Code:

**Contact Us For More Information**

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

**LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA**

\* Specification subject to error and may change without notice