



Specification Sheet

Lake Cable Quote Part #: C223CT-2960

Description: 22 AWG 3 conductors 7 strands tinned copper, PP insulated, unshielded with an overall PVC jacket approved 30V, 60°C (UL) AWM 2960 applications.

1. Conductor

- 1.1. AWG Size & Stranding: 22 AWG 7 Strands Class B
- 1.2. Material: Annealed Tinned copper
- 1.3. Conductor Count: 3 Conductors

2. Dielectric

- 2.1. Material: Polypropylene
- 2.2. Wall Thickness: 0.011"
- 2.3. Color Code: Red, Black, Green

3. Assembly

- 3.1. Cable Lay Length: 1.75" LHL (6.85 Tw/Ft)
- 3.2. Fillers: Fibrillated PP for roundness
- 3.3. Drain Wire: N/A
- 3.4. Shield: N/A

4. Jacket

- 4.1. Material: Polyvinylchloride
- 4.2. Wall Thickness: 0.035"
- 4.3. Diameter: 0.179"
- 4.4. Color: Black
- 4.5. Ripcord: No
- 4.6. Weight: 20 Lbs/Mft

5. Markings

- 5.1. Type: Cable permanently identified via marker threads
- 5.2. Legend: N/A
- 5.3. Footage Markers: No

6. Standards

- 6.1. UL recognized AWM Style 2960 30V 60°C
- 6.2. All materials used in the manufacture of this cables are RoHS compliant

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature

Company

ALL SPECIFIED PARAMETERS ARE NOMINAL AND SUBJECT TO VERIFICATION