





Aerospace Part#: 1381 PLENUM CABLE

DESCRIPTION

3 Conductors AWG 22/7x30 TC Unshielded FEP/FEP Gray CL2P CMP

PHYSICAL PROPERTIES

 Conductors
 Insulation

 # Conductors
 AWG
 Material
 Material
 Wall
 Finished OD

 3
 22/7x30
 Tinned Copper
 FEP
 .006"
 .042"

Outer Jacket Material Cabling

Jacket Material	Color	Wall	Overall O.D.	Lay
FEP	Gray	.010"	.110" Nom.	2" Lay on Cable

MECHANICAL PROPERTIES

Operating Temp	Total Weight	Bend Radius
Rated -80C to 200C	11 lbs/m	10 X OD

ELECTRICAL PROPERTIES

Max. Operating Voltage
UL Rated 300V Power Ltd.

INDUSTRY APPROVALS AND COMPLIANCE

Standards & Environmental Programs

Standards & Environmental Programs				
Reach / RoHS Compliant	YES			
Suitability	Indoor, Direct Burial, Wet Location			
Resistance	Oil, Gas, Sunlight, Abrasian, Acid			
Applications	Communications, Audio, Control, Instrumentation Remote, Signaling, Power-limited systems			
Flame Test	NFPA 262 / FT6			
NEC / (UL) Specification	CL2P / CMP			
CEC / C (UL) Specification	CMP			

MISCELLANEOUS

Markings: E111036 TYPE CL2P - E130356 TYPE CMP 22 AWG (UL), C(UL) FEP/FEP

Color Black / Red / White /

Code: Black / Red / White

Contact Us For More Information

T: 800.395.0200 F: 718.358.2522 E: sales@aerospacewire.com W: www.aerospacewire.com

LOW MINIMUM RUNS QUICK TURNAROUNDS CUSTOM CABLE SOLUTIONS MADE IN USA

^{*} Specification subject to error and may change without notice