

Written By:	scs	12/13/2013	Rev. 1	Added JM and Reference Numbers
Revised By:	scs	1/2/2013	Rev. 2	Change Cond #3 from Natural (Clear) to (Opaque)
Revised By:	scs	2/7/2014	Rev. 3	Added Drain Wire
Revised By:	scs	2/14/2014	Rev. 4	Added RoHS Compliance

2/15/14 Keturia Wilton approved

**Requirements**

Temperature: 90C  
Voltage: 300V

Approvals: None Applicable  
RoHS Compliant per 2011/65/EU

**Print**

Unprinted

**Color Code**

- 1. Black
- 2. Red
- 3. Natural (Opaque)

**Overall Cable Construction**

Cabling: Three conductors cabled together - No Fillers  
Binder: Fleece tape  
Drain Wire: 22 AWG, 26/36 tinned copper  
Shield: 36 AWG tinned copper braid, 95% coverage  
Separator: Tissue tape  
Jacket: .035" nominal wall of Mist Gray Pressured PVC  
.230"

**Components**

Three 22 AWG Insulated Conductors  
Conductor: 22 AWG, 26/36 tinned copper  
Insulation: .016" nominal wall of TPE (see color code)  
.062"

Description: Three 22 AWG Conductors  
Overall Braid Shield and PVC Jacket

JM Part Number: JM57091  
Reference: 2203C-8JM2

Date: 12/10/13

GENERAL PRODUCT SPECIFICATION  
Phone 800-316-8877 Fax 978-368-1275  
www.jamesmonroewire.com

